



# OWNER'S MANUAL

READ THIS MANUAL CAREFULLY,  
IT CONTAINS IMPORTANT SAFETY INFORMATION.



MINIMUM RECOMMENDED OPERATOR AGE: 16

**TRX250EX**  
**Sportrax250EX**


This manual should be considered a permanent part of the ATV and should remain with the ATV when it is resold.

This publication includes the latest production information available before printing. Honda Motor Co., Ltd. reserves the right to make changes at any time without notice and without incurring any obligation.

No part of this publication may be reproduced without written permission.

© Honda Motor Co., Ltd. 2003

**Honda TRX 250EX**  
**Sportrax 250EX**  
**OWNER'S MANUAL**



# Introduction

---

Congratulations on choosing your Honda ATV.

When you own a Honda, you're part of a worldwide family of satisfied customers — people who appreciate Honda's reputation for building quality into every product.

Your Honda was designed as a recreational ATV for off-road use by one rider only.

Before riding, take time to get acquainted with your ATV and how it works. To protect your investment, we urge you to take responsibility for keeping your ATV well maintained. Scheduled service is a must, of course. But it's just as important to observe the break-in guidelines, and perform all pre-ride and other periodic checks detailed in this manual.

We also recommend that you read this owner's manual before you ride. It's full of facts, instructions, safety information, and helpful tips. To make it easy to use, the manual contains a detailed list of topics at the beginning of each section, and both an in-depth table of contents and an index at the back of the book.

As you read this manual, you will find information that is preceded by a **NOTICE** symbol. This information is intended to help you avoid damage to your Honda, other property, or the environment.

Whenever you ride, tread lightly. By staying on established trails and riding only in approved areas, you help protect the environment and keep off-road riding areas open for the future.

# **Introduction**

---

If you have any questions, or if you ever need special service or repairs, remember that your Honda dealer knows your ATV best and is dedicated to your complete satisfaction.

Happy riding!

# A Few Words About Safety

---


Your safety, and the safety of others, is very important. And operating this ATV safely is an important responsibility.

To help you make informed decisions about safety, we have provided operating procedures and other information on labels and in this manual. This information alerts you to potential hazards that could hurt you or others.

Of course, it is not practical or possible to warn you about all hazards associated with operating or maintaining an ATV. You must use your own good judgment.

You will find important safety information in a variety of forms, including:

**Safety Labels** — on the ATV.

**Safety Messages** — preceded by a safety alert symbol  and one of three signal words: **DANGER**, **WARNING**, or **CAUTION**.

# A Few Words About Safety

---

These signal words mean:

 **DANGER**

You **WILL** be **KILLED** or **SERIOUSLY HURT** if you don't follow instructions.

 **WARNING**

You **CAN** be **KILLED** or **SERIOUSLY HURT** if you don't follow instructions.

 **CAUTION**

You **CAN** be **HURT** if you don't follow instructions.

**Safety Headings** — such as Important Safety Reminders or Important Safety Precautions.

**Safety Section** — such as ATV Safety.

**Instructions** — how to use this ATV correctly and safely.

This entire manual is filled with important safety information — please read it carefully.

# Contents

---

These pages give an overview of the contents of your owner's manual. The first page of each section lists the topics covered in that section.

<b>ATV Safety .....</b>	<b>1</b>
Important safety information you should know, plus a look at the safety-related labels on your ATV.	
<b>Instruments &amp; Controls.....</b>	<b>9</b>
The location and function of indicators and controls on your ATV and operating instructions for various controls and features.	
<b>Before Riding.....</b>	<b>25</b>
The importance of wearing a helmet and other protective gear, how to make sure you and your ATV are ready to ride, and important information about loading.	
<b>Basic Operation &amp; Riding .....</b>	<b>39</b>
How to start and stop the engine, shift gears, and brake. Also, riding precautions.	



# Contents

---

<b>Servicing Your Honda .....</b>	<b>71</b>
Why your ATV needs regular maintenance, what you need to know before servicing your Honda, an owner maintenance schedule, and instructions for specific maintenance and adjustment items.	
<b>Tips .....</b>	<b>145</b>
How to store and transport your ATV and how to be an environmentally-responsible rider.	
<b>Taking Care of the Unexpected .....</b>	<b>155</b>
What to do if you have a flat tyre, your engine won't start, etc.	
<b>Technical Information .....</b>	<b>169</b>
ID numbers, technical specifications, and other technical facts.	
<b>Table of Contents .....</b>	<b>180</b>
Sequential listing of topics in this owner's manual.	
<b>Index .....</b>	<b>186</b>

# ATV Safety

---

This section presents some of the most important information and recommendations to help you ride your ATV safely. Please take a few moments to read these pages. This section also includes information about the location of safety labels on your ATV.

Important Safety Information .....	2
Safety Labels.....	5

# Important Safety Information

---

Your ATV can provide many years of service and pleasure — if you take responsibility for your own safety and understand the challenges you can meet while riding.

There is much that you can do to protect yourself when you ride. You'll find many helpful recommendations throughout this manual. The following are a few that we consider most important.

## **Follow the Age Recommendation**

The minimum recommended age for this ATV model is 16. Children under age 16 should never operate this vehicle.

## **Always Wear a Helmet**

It's a proven fact: helmets significantly reduce the number and severity of head injuries. So always wear an approved motorcycle helmet. We also recommend that you wear eye protection, sturdy boots, gloves, and other protective gear (page 26 ).

## **Never Carry a Passenger**

Your ATV is designed for one person only. There are no handholds, footrests, or seat for a second person — so never carry a passenger. A passenger could interfere with your ability to move around to maintain your balance and control of the ATV.

# **Important Safety Information**

---

## **Ride Off-Road Only**

Your ATV is designed and manufactured for off-road use only. The tyres are not made for pavement, and the ATV does not have turn signals and other features required for use on public roads. If you need to cross a paved or public road, get off and walk your ATV across.

## **Take Time to Learn & Practice**

Even if you have ridden other ATVs, take time to become familiar with how this ATV works and handles. Practice in a safe area until you build your skills and get accustomed to the ATV's size and weight.

## **Be Alert for Off-Road Hazards**

The terrain can present a variety of challenges when you ride off-road. Continually “read” the terrain for unexpected turns, drop-offs, rocks, ruts, and other hazards. Always keep your speed low enough to allow time to see and react to hazards.

# Important Safety Information

---

## **Ride within Your Limits**

Pushing limits is another major cause of ATV accidents. Never ride beyond your personal abilities or faster than conditions warrant. Remember that alcohol, drugs, fatigue, and inattention can significantly reduce your ability to make good judgments and ride safely.

## **Don't Drink and Ride**

Alcohol and riding don't mix. Even one drink can reduce your ability to respond to changing conditions, and your reaction time gets worse with every additional drink. So don't drink and ride, and don't let your friends drink and ride either.

## **Keep Your Honda in Safe Condition**

It's important to keep your ATV properly maintained and in safe riding condition. Having a breakdown can be difficult, especially if you are stranded off-road far from your base. To help avoid problems, inspect your ATV before every ride and perform all recommended maintenance.

# Safety Labels

---

Your ATV comes with several labels containing important safety information. Anyone who rides the vehicle should read and understand this information before riding.

The labels should be considered permanent parts of the vehicle. If a label comes off or becomes hard to read, contact your Honda dealer for replacements.

# Safety Labels

---



## WARNING

Improper tire pressure or overloading can cause loss of control.


Loss of control can result in severe injury or death.

Cold tire pressure :




Front :  $30 \pm 4 \text{ kPa}$   $0.30 \pm 0.04 \text{ kgf/cm}^2$   $4.4 \pm 0.6 \text{ psi}$ .

Rear :  $20 \pm 3 \text{ kPa}$   $0.20 \pm 0.03 \text{ kgf/cm}^2$   $2.9 \pm 0.4 \text{ psi}$ .

Maximum weight capacity ; 110kg (243lbs.)



# Safety Labels





# Indicators & Controls

---

This section shows the location of all indicators and controls you would normally use before or while riding your ATV.

The items listed on this page are described in this section. Instructions for other components are presented in other sections of this manual where they will be most useful.

Component Locations .....	11
Indicators.....	14
Reverse and Neutral Indicators Lamps .....	14

(cont'd)


# Indicators & Controls

---

Control and Features .....	15
Fuel Valve .....	15
Choke Knob .....	16
Ignition Switch .....	17
Start Button .....	18
Engine Stop Switch .....	18
Headlight Switch .....	19
Headlight Dimmer Switch .....	19
Throttle Lever .....	20
Reverse Selector Knob .....	21
Front Brake Lever .....	22
Rear Brake Lever .....	22
Rear Brake Pedal .....	22
Parking Brake .....	22
Flag Pole Bracket .....	23


# Component Locations

---




# Component Locations

---



# Component Locations

---



# Indicators

---


## Reverse and Neutral Indicator Lamps

The reverse indicator lamp ( 1 ) and the neutral indicator lamp ( 2 ) are next to the ignition switch.

The reverse indicator lamp will light when the transmission is in reverse and the ignition switch is ON ( I ).

The neutral indicator lamp will light when the transmission is in neutral and the ignition switch is ON ( I ).

If one of these indicators does not come on when it should, have your Honda dealer check for burned-out bulbs or other problems.




(1) reverse indicator lamp

(2) neutral indicator lamp

# Controls & Features

## Fuel Valve

### LEFT SIDE



(1) fuel valve

The manual fuel valve is located on the left side of the fuel tank.

The three-way fuel valve is used to control the flow of fuel from the fuel tank to the carburetor.

ON — normal position for riding.

OFF — for parking, storing, or transportation.

RES — for extra fuel to get to a gas supply for refueling.

### Reserve Fuel

Remember to check that the fuel valve is in the ON position each time you refuel. If the valve is left in the RES position, you may run out of fuel with no reserve.

For complete information about fueling your ATV, see page 87 .


# Controls & Features

---

## Choke Knob

N

### LEFT HANDLEBAR



(1) choke knob

(A) fully ON

(B) half way position

(C) fully OFF

The choke knob may be used when starting the engine. See page 47 .




# Controls & Features

## Ignition Switch

The ignition switch is used for starting and stopping the engine (page 46 ). Insert the key and turn it to the right for the ON position.

Key Position	Function
ON ( I )	Electrical circuits on.
OFF ( O )	No electrical circuits function.

## CENTRE OF HANDLEBAR




(1) ignition switch

I ON  
O OFF

# Controls & Features

## Start Button

### LEFT HANDLEBAR



(1) start button

(2) engine stop switch

Ⓢ START

ⓧ OFF

○ RUN

The start button ( 1 ) is used for starting the engine. Pushing the button in starts the engine. See *Starting Procedure*, page 47 .

When the start button is pushed, the starter motor will crank the engine. The starter motor will not operate if the engine stop switch is in the OFF position when the start button is pushed.

## Engine Stop Switch

The engine stop switch ( 2 ) is used to stop the engine in an emergency. To operate, press the switch to either OFF position. The switch must be in the RUN position to start the engine, and it should normally remain in the RUN position even when the engine is OFF.


If your ATV is stopped with the ignition switch ON and the engine stop switch OFF, the battery will discharge. Turn the ignition switch OFF to prevent battery discharge.

# Controls & Features

## Headlight Switch



LEFT HANDLEBAR



(1) headlight switch

(2) headlight dimmer switch

☀ ON  
• OFF  
≡D HI  
≡D LO

The headlight switch ( 1 ) is used to turn the headlight ON ( ☀ ) or OFF ( • ). To operate, turn the switch to ON ( ☀ ) or OFF ( • ).

## Headlight Dimmer Switch




The headlight dimmer switch ( 2 ) is used to change between the high and low beams of the headlight. To operate, turn the switch to HI ( ≡D ) for high beam, LO ( ≡D ) for low beam.

# Controls & Features

---

## Throttle Lever

### RIGHT HANDLEBAR



(1) throttle lever

(A) to open the throttle

The throttle controls engine rpm (speed). To increase engine rpm, press the lever ( 1 ) with your thumb. To reduce engine rpm, release pressure on the lever. The throttle will automatically return to the closed position (engine idle) when you remove your thumb.


# Controls & Features

---

## Reverse Selector Knob

The reverse selector knob ( 1 ), located on the rear brake lever ( 2 ), is used to shift into reverse. To operate, with your ATV stopped and the transmission in neutral, push in the knob, squeeze the rear brake lever, then depress the gearshift pedal. See *Riding in Reverse*, page 53 .

## LEFT HANDLEBAR



(1) reverse selector knob

(2) rear brake lever

# Controls & Features

---

## Front Brake Lever

The front brake lever is used to slow or stop your ATV. To operate, pull the lever. For information on braking techniques, see page 55.

## Rear Brake Lever


The rear brake lever is used to slow or stop your ATV. To operate, pull the lever. For information on braking techniques, see page 55.

## Rear Brake Pedal

The rear brake pedal is used to slow or stop your ATV. To operate, depress the pedal. For information on braking techniques, see page 55.

## Parking Brake

### LEFT HANDLEBAR



(1) lock lever

(A) to lock


(2) rear brake lever/  
parking lever

The lock lever ( 1 ) on the rear brake lever ( 2 ) allows it to be used as a parking brake. To operate, first squeeze the rear brake lever using your left hand and then lock it with the lock lever using your right hand. See *Parking* page 69 .

# Controls & Features

## Flag Pole Bracket

RIGHT REAR



(1) flag pole bracket

Flag poles are optional equipment available from your Honda dealer. To mount a pole in the bracket ( 1 ), follow the instructions that come with the flag pole kit.

Flag poles are required in some riding areas. Check local regulations before riding.

# Before Riding

---

Before each ride, you need to make sure you and your Honda are both ready to ride. To help get you prepared, this section discusses how to evaluate your riding readiness, what items you should check on your ATV, and adjustments to make for your comfort, convenience, or safety. This section also includes important information about loading.

Are You Ready to Ride ? .....	26
Protective Apparel.....	26
Rider Training .....	28
Age Recommendation.....	29
No Passengers .....	29
No Alcohol or Drugs.....	30
Is Your ATV Ready to Ride ?.....	31
Pre-ride Inspection .....	31
Load Limits & Guideline .....	34
Loading .....	34



# Are You Ready to Ride?

---

Before you ride your ATV for the first time, we urge you to:

- Read this owner's manual and the labels on your ATV carefully.
- Make sure you understand all the safety messages.
- Know how to operate all the controls.

Before each ride, be sure:

- You feel well and are in good physical and mental condition.
- You are wearing an approved motorcycle helmet (with chin strap tightened securely), eye protection, and other protective clothing.
- You don't have any alcohol or drugs in your system.

## Protective Apparel

For your safety, we strongly recommend that you always wear an approved motorcycle helmet, eye protection, boots, gloves, long pants, and a long-sleeved shirt or jacket whenever you ride.

Although complete protection is not possible, wearing proper gear can reduce the chance of injury when you ride.

Following are suggestions to help you choose the proper gear.

### Helmets and Eye Protection

Your helmet is your most important piece of riding gear because it offers the best protection against head injuries. A helmet should fit your head comfortably and securely.

# Are You Ready to Ride?

---

An open-face helmet offers some protection, but a full-face helmet offers more. Always wear a face shield or goggles to protect your eyes and help your vision.

## **WARNING**

Operating this ATV without wearing an approved motorcycle helmet, eye protection, and protective clothing could increase your chances of severe injury or death in the event of an accident.

Always wear an approved motorcycle helmet that fits properly and wear eye protection (goggles or face shield), gloves, boots, long-sleeved shirt or jacket and long pants.

### Additional Riding Gear

In addition to a helmet and eye protection, we also recommend:

- Sturdy off-road motorcycle boots to help protect your feet, ankles, and lower legs.
- Off-road motorcycle gloves to help protect your hands.
- Riding pants with knee and hip pads, a riding jersey with padded elbows, and a chest/shoulder protector.

# Are You Ready to Ride?

---

## Rider Training

Developing your riding skills is an on-going process. Even if you have ridden other ATVs, take time to become familiar with how this ATV works and handles. Practice riding the ATV in a safe area to build your skills. Do not ride in rough terrain until you get accustomed to the ATV's controls, and feel comfortable with its size and weight.

### **⚠ WARNING**

Operating this ATV without proper instruction could increase your risk of an accident which could lead to serious injury or death.

Beginning and inexperienced operators should complete the certified training course offered by Honda. They should then regularly practice the skills learned in the course and the operating techniques described in the owner's manual.

# Are You Ready to Ride?

---

## Age Recommendation

The minimum recommended age for this ATV model is 16. For safety, never let children under 16 years old operate this vehicle.

### **WARNING**

A child using an ATV that is not recommended for their age could lose vehicle control while riding, resulting in severe injury or death.

A child under 16 should never operate an ATV with engine size greater than 90cc.

## No Passengers

This ATV is designed as an operator-only vehicle. The long seat is designed to allow the rider to change body position, not for carrying a passenger. Never let a passenger ride on the seat or on the front or rear cargo racks.

### **WARNING**

Carrying a passenger on this ATV greatly reduces your ability to balance and control this ATV and could cause a crash and you or your passenger could be injured or killed.

Never carry a passenger on this ATV.

# Are You Ready to Ride?

---

## No Alcohol or Drugs

Alcohol, drugs and ATVs don't mix. Even a small amount of alcohol can impair your ability to operate an ATV safely. Likewise, drugs — even if prescribed by a physician — can be dangerous while operating an ATV. Consult your doctor to be sure it is safe to operate a vehicle after taking medication.

### **WARNING**

Operating this ATV after consuming alcohol or drugs can seriously affect your judgement, cause you to react more slowly, affect your balance and perception, and result in serious injury or death.

Never consume alcohol or drugs before or while operating this ATV.

# Is Your ATV Ready to Ride?

---

Before each ride, it's important to inspect your ATV and make sure any problem you find is corrected. A pre-ride inspection is a must, not only for safety, but because having a breakdown, or even a flat tyre, can be a major inconvenience.

If your ATV has overturned or been involved in a collision, do not ride the vehicle until it has been inspected by your Honda dealer. There may be damage or other problems you cannot see.

## **WARNING**

Improperly maintaining this ATV or failing to correct a problem before riding can cause a crash in which you can be seriously hurt or killed.

Always perform a pre-ride inspection before every ride and correct any problems.

## **Pre-ride Inspection**

Check the following items before you get on the ATV:

### *Engine Oil*

Check the level and add oil if needed (page 90 ).

Check for leaks.

### *Fuel*

Check the level and add fuel (page 87 ) if needed. Also make sure the fuel fill cap is securely fastened.

Check for leaks.

# Is Your ATV Ready to Ride?

---

<i>Tyres</i>	Use a gauge to check the air pressure. Adjust if needed. Also look for signs of damage or excessive wear (page 129 ).
<i>Nuts &amp; Bolts</i>	Check the wheels to see that the axle nuts are tightened. Use a wrench to make sure all accessible nuts, bolts, and fasteners are tight.
<i>Underbody &amp; Exhaust System</i>	Check for, and remove, any dirt, vegetation or other debris that could be a fire hazard or interfere with the proper operation of the vehicle.
<i>Air Cleaner Housing Drain Tube</i>	Check for deposits in the drain tube. If necessary, clean the tube (page 102 ) and check the air cleaner housing.
<i>Leaks, Loose Parts</i>	Walk around your ATV and look for anything that appears unusual, such as a leak or loose cable.
<i>Cable</i>	Check the cable housings for wear. Check the fittings for looseness. Replace or tighten as needed.

# Is Your ATV Ready to Ride?

---

Check these items after you get on the ATV:

<i>Throttle</i>	Check the freeplay and adjust if needed. Press the throttle to make sure it moves smoothly without sticking, and snaps shut automatically when it is released, in all steering positions (page 103 ).
<i>Brakes</i>	Squeeze the front and rear brake levers and step on the rear brake pedal to check that the controls operate normally. Check for proper freeplay (page 120 ). Make sure there is no brake fluid leakage (page 117 ).
<i>Headlight and Headlight Dimmer Switch</i>	Check for proper function (page 19 ).
<i>Engine Stop Switch</i>	Check for proper function (page 18 ).
<i>Steering</i>	Check that the wheels turn properly as you steer the handlebar.

Remember, be sure to take care of any problem you find, or have your Honda dealer correct it before you ride.



# Load Limits & Guidelines

---

Your Honda was designed as a rider-only ATV. It was not designed to carry a passenger or cargo. A passenger or cargo could interfere with your ability to move around to maintain your balance and control of the ATV.

In addition, exceeding the weight limits or carrying an unbalanced load can seriously affect your ATV's handling, braking, and stability. Adding accessories or making modifications that change this ATV's design and performance can also make it unsafe. Also, the weight of any accessories will reduce the maximum load the ATV can carry.

More specific information on load limits, accessories, and modifications follows.

## Loading

How much weight you put on your ATV, and how you load it, are important to your safety. If you decide to carry cargo, you should be aware of the following information.

### **WARNING**

Overloading, improper loading, or carrying a passenger can cause a crash and you can be seriously hurt or killed.

Follow all load limits and other loading guidelines in this manual.

# Load Limits & Guidelines

---

## **Load Limits**

Following are the load limits for your ATV:

There are limits to how much weight can be carried on your ATV.

The following load limits apply to standard equipment only. Modifying your ATV, using non-standard equipment, or riding on terrain that is not flat and smooth could further reduce these limits.

**maximum weight capacity      110 kg (243 lbs)**  
(includes the weight of the rider, all cargo, and accessories.)

The weight of added accessories will reduce the maximum cargo weight you can carry.

# Load Limits & Guidelines

---

## **Loading Guidelines**

As discussed on page 34 , we recommend that you do not carry any cargo on this ATV. However, if you decide to carry cargo, ride at reduced speeds and follow these common-sense guidelines.

Carrying cargo or pulling a trailer will affect how your ATV handles and greatly reduce its ability in accelerating, braking and making turns and other maneuvers.

Be sure to observe the weight limits and follow these guidelines:

- Check that the tyres are properly inflated.
- Never ride with a passenger. The ATV is not designed to carry a passenger.
- Do not tow another vehicle.
- Make sure all cargo is secured before riding.
- Never exceed the maximum weight limit.
- Allow extra room for starting, stopping and turning whenever you carry cargo or pull a trailer.
- Avoid riding on steep slopes when carrying cargo or pulling a trailer.
- Never cross a slope when towing a trailer.

# Accessories & Modifications

---

Modifying your ATV or using non-Honda accessories can make your ATV unsafe.

Before you consider making any modifications or adding an accessory, be sure to read the following information.

## **WARNING**

Improper accessories or modifications can cause a crash in which you can be seriously hurt or killed.

Follow all instructions in this owner's manual regarding accessories and modifications.

### Accessories

We strongly recommend that you use only genuine Honda accessories that have been specifically designed and tested for your ATV. Because Honda cannot test all other accessories, you must be personally responsible for proper selection, installation, and use of non-Honda accessories.

Check with your Honda dealer for assistance and always follow these guidelines:

- Make sure the accessory does not obscure any lights, reduce ground clearance, limit suspension travel or steering travel, or interfere with operating any controls.
- Make sure the accessory does not interfere with your ability to shift body position on the seat or operate hand and foot controls.
- Do not add any electrical equipment that will exceed the vehicle's electrical system capacity (page 174 ). A blown fuse can cause a loss of lights or engine power (page 164 ).

# Accessories & Modifications

---

## **Modifications**

We strongly advise you not to remove any original equipment or modify your ATV in any way that would change its design or operation. Such changes could seriously impair your ATV's handling, stability, and braking, making it unsafe to ride.

We also advise you not to make any modifications or remove any equipment (such as the USDA qualified spark arrester or emission control system components) that would make your ATV illegal in your area.

Removing or modifying your lights, exhaust system, emission control system, or other equipment can also make your ATV illegal.

# Basic Operation & Riding

---

This section gives basic riding instructions, including how to start and stop your engine, and how to use the throttle and brakes. and what to do when you're through riding.

To protect your new engine and enjoy optimum performance and service life, refer to Break-in Guidelines (page 176).

For information about carburetor adjustment for riding at high altitude, see page 177.

Safe Riding Precautions .....	41
Off-Road Use Only .....	41
Keep Hands and Feet on Controls .....	42
Control Speed .....	43
Use Care on Unfamiliar or Rough Terrain .....	44
Do Not Perform Stunts .....	45
Starting & Stopping the Engine .....	46
Preparation .....	46
Starting Procedure .....	47
Flooded Engine .....	50
How to Stop the Engine .....	50
Shifting Gears .....	51
Riding in Reverse .....	53

(cont'd)

# Basic Operation & Riding

---

Braking.....	55
Riding Your ATV .....	57
Making Turns.....	57
Skidding or Sliding .....	59
Riding Up Hills .....	60
Riding Down Hills .....	64
Crossing or Turning on Hills or Slopes.....	65
Riding Over Obstacles .....	67
Riding Through Water .....	68
Parking .....	69

# Safe Riding Precautions

---

Before riding your ATV for the first time, please review the *ATV Safety* section beginning on page 1, and the *Before Riding* section beginning on page 25.

Even if you have ridden other ATVs, take time to become familiar with how this ATV works and handles. Practice in a safe area until you build your skills and get accustomed to the ATV's size and weight.

## Off-Road Use Only

Your ATV and its tyres are designed and manufactured for off-road use only, not for pavement. Riding on pavement can affect handling and control. You should not ride your ATV on pavement.

### **WARNING**

Operating this ATV on paved surfaces may seriously affect handling and control of the ATV, and may cause the vehicle to go out of control.

Never operate the ATV on any paved surfaces, including sidewalks, driveways, parking lots and streets.

When riding off-road, also remember to always obey local off-road riding laws and regulations. Obtain permission to ride on private property. Avoid posted areas and obey “no trespassing” signs.

(cont'd)



# Safe Riding Precautions

---

You should never ride your ATV on public streets, roads or highways, even if they are not paved. Drivers of street vehicles may have difficulty seeing and avoiding you, which could lead to a collision. In many states it is illegal to operate ATVs on public streets, roads and highways.

## WARNING

Operating this ATV on public streets, roads or highways could cause you to collide with another vehicle.

Never operate this ATV on any public street, road or highway, even a dirt or gravel one.

## **Keep Hands and Feet on Controls**

Always keep both hands on the handlebars and both feet on the footpegs when riding your ATV. This is important to maintain your balance and to control the vehicle. Removing even one hand from the handlebars or one foot from the footpegs can reduce your ability to control the ATV or could cause you to lose your balance and fall off the ATV.

## WARNING

Removing hands from handlebars or feet from footpegs during operation can reduce your ability to control the ATV or could cause you to lose your balance and fall off of the ATV.

Always keep both hands on the handlebars and both feet on the footpegs of your ATV during operation.

# Safe Riding Precautions

---

## Control Speed

Riding at excessive speed increases the chance of an accident. In choosing a proper speed, you need to consider the capability of your vehicle, the terrain, visibility and other operating conditions, plus your own skills and experience.

### **WARNING**

Operating this ATV at excessive speeds increases your chances of losing control of the ATV, which can result in an accident.

Always go at a speed that is proper for your vehicle, the terrain, visibility and other operating conditions, and your experience.

# Safe Riding Precautions

---

## Use Care on Unfamiliar or Rough Terrain

Before riding in a new area, always check the terrain thoroughly. Don't ride fast on unfamiliar terrain or when visibility is limited. (It's sometimes difficult to see obstructions like hidden rocks, bumps, or holes in time to react.)

### **WARNING**

Failure to use extra care when operating this ATV on unfamiliar terrain could result in the ATV overturning or going out of control.

Go slowly and be extra careful when operating on unfamiliar terrain. Always be alert to changing terrain conditions when operating the ATV.

# Safe Riding Precautions

---

Never ride past the limit of visibility. Maintain a safe distance between your ATV and other off-road vehicles. Always exercise caution, and use extra care on rough, slippery and loose terrain.

## **WARNING**

Failure to use extra care when operating on excessively rough, slippery or loose terrain could cause loss of traction or vehicle control, which could result in an accident, including an overturn.

Do not operate on excessively rough, slippery or loose terrain until you have learned and practiced the skills necessary to control the ATV on such terrain. Always be especially cautious on these kinds of terrain.

## **Do Not Perform Stunts**

You should always operate your ATV in a safe and reasonable manner. When riding, always keep all four wheels on the ground.

## **WARNING**

Attempting wheelies, jumps, and other stunts increases the chance of an accident, including an overturn.


Never attempt stunts, such as wheelies or jumps. Don't try to show off.

# Starting & Stopping the Engine

Always follow the proper starting procedure described below.

For your safety, avoid starting or operating the engine in an enclosed area such as a garage. Your ATV's exhaust contains poisonous carbon monoxide gas which can collect rapidly in an enclosed area and cause illness or death.

## Preparation



1. Before starting, Select a level surface and lock the parking brake (page 22 ).
2. Turn the fuel valve ( 1 ) and ignition switch ( 2 ) to ON ( I ).

Confirm the following:

- The transmission is in NEUTRAL (neutral indicator ( 3 ) light ON).
- The engine stop switch ( 4 ) is set to RUN ( O ).

# Starting & Stopping the Engine


## Starting Procedure

To restart a warm engine, follow the procedure for “*High Air Temperature.*”

The starter motor will operate only when the transmission is in neutral.

Normal Air Temperature 10° – 35°C (50° – 95°F)

### CENTRE OF HANDLEBAR



(1) choke knob

(A) fully ON

(B) half way position

(C) fully OFF

1. Pull the choke knob ( 1 ) up all the way to fully ON (A) position, if the engine is cold.
  2. With the throttle slightly open, press the start button.
- Pressing the electric start button for more than 5 seconds at a time may cause the starter to overheat and damage the starter. Release the starter button for approximately 10 seconds before pressing it again.

(cont'd)


# Starting & Stopping the Engine

---

3. Immediately after the engine starts, push the choke knob down to the halfway position (B).
4. Warm up the engine by opening and closing the throttle slightly.
5. After the engine has warmed up, push the choke knob down all the way to fully OFF (C).
6. If idling is unstable, open the throttle slightly.

High Air Temperature 35°C (95°F) or above

## LEFT HANDLEBAR



(1) start button

1. Do not use the choke.
2. With the throttle slightly open, press the start button (1).

# Starting & Stopping the Engine

---

## Low Air Temperature 10°C (50°F) or below

1. Follow steps 1 – 2 under “*Normal Air Temperature.*”
2. Warm up the engine by opening and closing the throttle slightly.
3. When the engine begins to run slightly rough, push the choke knob down to the halfway position (B).
4. Continue warming up the engine until it runs smoothly and responds to the throttle, then push the choke knob down all the way to fully OFF (C).
5. If idling is unstable, open the throttle slightly.

### **NOTICE**

*Extended use of the choke may impair piston and cylinder wall lubrication and shorten the life of the engine.*

Do not race the engine during the warm-up period.

Racing a cold engine wastes fuel and increases engine wear.





# Starting & Stopping the Engine

---

## Flooded Engine

If the engine fails to start after repeated attempts, it may be flooded with excess fuel. To clear a flooded engine:


1. Move the engine stop switch to OFF (  ).
2. Push the choke knob down all the way to fully OFF.
3. Open the throttle fully.
4. Press the start button for 5 seconds.
5. Wait 10 seconds, then turn the engine stop switch to RUN (  ).
6. Repeat the “Normal Air Temperature” starting procedure, but don’t use the choke.


If the engine still won’t start, refer to *If Your Engine Quits or Won’t Start*, page 158.

## How to Stop the Engine

### Normal Engine Stop

To stop the engine, make sure the transmission is in neutral by checking that the neutral indicator lights, and turn the ignition switch OFF.

The engine stop switch should normally remain in the RUN (  ) position even when the engine is OFF.


If your ATV is stopped with the engine stop switch OFF (  ) and the ignition switch ON, the battery will discharge.

### Emergency Engine Stop

To stop the engine in an emergency, use the engine stop switch. To operate, move the switch to either OFF position.

# Shifting Gears

## UPSHIFTING SEQUENCE



## DOWNSHIFTING SEQUENCE

Your ATV has five forward gears: 1, 2, 3, 4, and 5.

The gearshift pedal is located near the left footpeg. One full stroke of the pedal shifts the transmission to the next higher or lower gear in the shifting sequence. The pedal automatically returns to the horizontal position when released.

To upshift to a higher gear, put the toe of your boot under the gearshift pedal and raise the pedal one full stroke. To downshift, step on the gearshift pedal and depress the pedal one full stroke.

# Shifting Gears

---

After starting the engine and letting it warm up, follow these procedures:

1. With the transmission in neutral, release the parking brake, but continue squeezing the rear brake lever.
2. With the throttle closed, raise the gearshift pedal one full stroke to shift into 1st (first) gear.
3. Release the rear brake lever and increase engine speed by gradually opening the throttle.
4. When speed increases, release the throttle and shift to 2nd gear by raising the gearshift pedal one full stroke.
5. Repeat this sequence to progressively upshift to 3rd, 4th and 5th (top) gear.
6. To downshift, reverse this sequence. Remember to close the throttle each time you shift to the next lower gear.

Learning when to shift gears comes with experience. Keep the following tips in mind:

- As a general rule, shift while moving in a straight line.
- Close the throttle completely before shifting. Improper shifting may damage the engine, transmission, and drive train.
- Upshift to a higher gear or reduce throttle before engine rpm (speed) gets too high. Learn the relationship between engine sound and the normal shifting points.
- Downshift to a lower gear before you feel the engine laboring (lugging) at low rpm.
- Avoid downshifting to help slow your ATV when engine rpm is high. Downshifting when engine speed is near its allowable maximum may over-rev the engine and cause possible damage.
- To prevent transmission damage, do not coast or tow the ATV for long distances with the engine off.
- Ride in the highest gear that lets the engine run and accelerate smoothly. This will give you good fuel economy and effective emissions control.

# Riding in Reverse

---

If you need to ride in reverse, make sure the area behind you is clear and only operate the ATV at low speed.

## **WARNING**

Improperly operating in reverse could cause you to hit an obstacle or person behind you, resulting in serious injury.

Make sure there are no obstacles or people behind you before selecting reverse gear. When it is safe to proceed, go slowly.

1. Bring the vehicle to a complete stop, then make sure the transmission is in neutral.
2. Be sure there are no obstacles or people in the way.
3. While pushing the reverse selector knob in, squeeze the rear brake lever, then depress the gearshift pedal.
4. Release the rear brake lever.
5. Open the throttle gradually and ride slowly. Do not open the throttle suddenly or make abrupt turns.

(cont'd)

# Riding in Reverse

---

6. To stop, close the throttle and gradually apply both the front and rear brakes. Do not abruptly apply the rear brake by itself.
7. To shift out of reverse and into neutral, raise the gearshift pedal one stroke.

## **WARNING**

Applying only the rear brake abruptly when operating in reverse gear could cause the front wheels to lift off the ground and the ATV could overturn backwards.

Carefully apply both the front and rear brakes when stopping in reverse gear.

Your ATV is equipped with disk brakes on both front wheels which are hydraulically activated by operating the right brake lever. A single drum brake on the rear axle housing is mechanically activated by depressing the brake pedal or operating the left brake lever.

As a general rule, the front braking system provides about 70 percent of total stopping power.

For full braking effectiveness, use both the pedal and lever simultaneously. Using both braking systems will stop your ATV faster with greater stability.

To slow or stop, apply the brake lever and brake pedal smoothly, while downshifting to match your speed.

Gradually increase braking as you feel the brakes slowing your speed. The increase in engine compression from downshifting will help slow your ATV.

Applying the brakes too hard may cause the wheels to lock and slide, reducing control of your ATV. If this happens, release the brake controls, steer straight ahead until you regain control, then reapply the brakes more gently.

When possible, reduce your speed or complete braking before entering a turn. Avoid braking or closing the throttle quickly while turning. Either action may cause one or more wheels to slip and reduce your control of your ATV.

# Braking

---

Your ability to brake in a turn and to brake hard in an emergency situation are important riding skills.

When descending a long, steep grade, use engine compression braking by downshifting, with intermittent use of both brakes. Continuous brake application can overheat the brakes and reduce their effectiveness.

Riding with your foot resting on the brake pedal or your hands on the brake levers may overheat the brakes, reducing effectiveness.

For information on how to apply the brakes in various riding situations, see the following section, *Riding Your ATV*.

## Making Turns

Learn how to turn your ATV properly. Practice the techniques outlined in this section on level ground and at low speeds until you are confident in making turns.

### **WARNING**


Turning improperly can make the ATV to go out of control, causing a collision or overturn.

- Always follow proper procedures for turning as described in this owner's manual.
- Practice turning at low speeds before attempting to turn at faster speeds.
- Do not turn at excessive speeds.



# Riding Your ATV

---



Lean your body to the inside of a turn and forward.

To make a turn on level ground: Steer the handlebar and lean your body toward the inside of the turn. Leaning helps balance the vehicle, and it feels more comfortable. Leaning into a turn is an important technique to master in riding an ATV.

To make a sharp turn at low speed: It helps to shift your body slightly forward on the seat, and lean inside, as you steer the handlebar. Shifting weight forward allows the rear wheels to turn easier, and it also improves front-wheel steering.

To make a turn from a full stop: Apply the throttle gradually when you turn and start up at the same time. Remember to shift your body forward to make sharp low-speed turns and whenever you turn while accelerating from a full stop.

# Riding Your ATV

---

## Skidding or Sliding

The terrain surface can be a major factor affecting turns. Skidding during a turn is more likely to occur on slippery surfaces, such as snow, ice, mud and loose gravel. If you skid on ice, you may lose all directional control. To avoid skidding on slippery terrain, keep your speed low and ride with caution.

### **WARNING**

Skidding or sliding improperly may cause you to lose control of this ATV. You may also regain traction unexpectedly, which may cause the ATV to overturn.

Learn to safely control skidding by practicing at low speeds and on level, smooth terrain.

If your ATV skids sideways during a turn, steer in the direction of the skid. Avoid hard braking or accelerating until you have regained directional control.

# Riding Your ATV

---

## Riding Up Hills

The ATV's ability to safely climb hills largely depends on the rider's skill and judgment. Begin by practicing on smooth, gentle slopes. As you gain experience, you'll learn the hazards and your own limitations. You may then proceed to ride on more difficult terrain. However, you must be able to decide which hills or hazards might cause the ATV to overturn. Avoid excessively steep hills.

### **WARNING**

Operating on excessively steep hills can cause the vehicle to overturn more easily than operating on level surfaces or small hills.

Never operate the ATV on hills too steep for the ATV or for your abilities.

When climbing hills, you must shift weight toward the front wheels to help keep them on the ground. To do this, shift your body slightly forward on the seat and lean forward. For greater weight shift, move your body farther forward and lean forward.


### **WARNING**

Climbing hills improperly could cause loss of control or cause the ATV to overturn.

Always follow proper procedures for climbing hills as described in this owner's manual.

# Riding Your ATV

---



Shift weight forward when climbing hills.

- Always check the terrain carefully before you start up any hill.
- Never climb hills with excessively slippery or loose surfaces.
- To climb a hill, take a running start in an appropriate gear and speed for the conditions. Maintain a steady speed as you ascend the hill.
- Never open the throttle suddenly or make sudden gear changes. The ATV could flip over backward.
- Never go over the top of any hill at high speed. An obstacle, a sharp drop, or another vehicle or person could be on the other side of the hill.

# Riding Your ATV

---

## **Stalling the ATV and/or Rolling Backwards:**

If you incorrectly estimate climbing capability or terrain conditions, the ATV may not have enough power or traction to continue uphill. If this happen, the ATV can stall and/or roll backwards.

### **⚠ WARNING**

Stalling, rolling backwards or improperly dismounting while climbing a hill could result in the ATV overturning.

Always follow proper procedures for climbing a hill as described in this owner's manual.

## What to do if the ATV stalls or rolls backwards when climbing a hill:

If you are about to lose all forward speed:

1. Using the front and rear brakes together, bring the ATV to a stop with the vehicle pointed straight uphill.
2. Get off the ATV while you continue holding the brakes.
3. Shift into neutral, set the parking brake and turn the engine off.
4. Then assess the situation.

If the ATV starts rolling backwards before you begin braking:

1. Keep your weight uphill.
2. Carefully apply the front brakes first, then carefully apply the rear brake. Do not apply the rear brake only or abruptly if you are rolling backwards, or the vehicle may overturn.

If the ATV continues sliding backwards:

After you've applied the brakes, get off and away from the vehicle.

# Riding Your ATV

---


## What to do after the ATV has stalled or rolled backwards:

If the hill is too steep or too slippery, or if you have any doubt whether you can safely walk the ATV back down the hill, leave the vehicle where it is and get help. If possible, block the wheels so the vehicle doesn't roll backwards.

If the hill is not too steep and you have good footing, you may be able to walk the ATV back down the hill. Make sure your intended path is clear in case you lose control of the ATV.



Be sure your legs are clear of the wheels.



Body position for backing down a hill.

1. Stand with your body facing downhill, beside the vehicle so you can reach the front brake lever with your left hand.
2. Be sure your legs are clear of the wheels.  
Check your footing.
3. Slowly and carefully back the ATV down the hill using the front brake lever to control speed.
4. If you lose control of the ATV, for your safety, get away from the vehicle.

# Riding Your ATV

---


## Riding Down Hills

It's usually advisable to descend hills with the ATV pointed straight downhill. Avoid angles that would cause the vehicle to lean sharply to one side.

### **WARNING**

Going down a hill improperly could cause loss of control or cause the ATV to overturn.

Always follow proper procedures for going down hills as described in this owner's manual.



On downhills, shift your weight back.

As you approach a downhill, stop and survey the terrain below. Never ride past the limit of your visibility. Never go down a hill at high speed.

# Riding Your ATV

---

When you've selected a safe downhill path, shift into a lower gear, shift your weight back with your arms extended and braced against the handlebar, then go down slowly with the throttle closed.

Use mainly the rear brake to control speed. Avoid using either the front brake or rear brake hard or abruptly when riding down hills.

Remember, braking effectiveness is reduced on any hill with a loose surface.

## **Crossing or Turning on Hills or Slopes**

Riding on hills or slopes is different from riding on level terrain. Be careful when riding on any hill. Make sure that you practice on gentle, smooth slopes before attempting to ride on steeper or more difficult terrain.

### **WARNING**

Improperly crossing hills or turning on hills could cause loss of control or cause the ATV to overturn.

Always follow proper procedures for crossing or turning on slopes as described in this Owner's Manual. Avoid crossing steep hills if possible.



# Riding Your ATV

---

## Crossing Hills or Slopes

- To maintain balance and stability when riding across a slope, you need to shift weight toward the uphill side of the vehicle. To do this, move your body off the centre of the seat and lean toward the uphill side.
- On a slippery or loose surface, you may also need to steer slightly uphill to maintain a straight course across the slope.
- Avoid crossing hills that are excessively steep, slippery or rough.



Shift weight uphill when crossing slopes.

## Making Turns on Slopes

- Compared to riding on level ground, you may need to shift more weight and lean more when making turns on slopes.
- Do not make turns on any slopes until you have first mastered the techniques for making turns on level terrain.

# Riding Your ATV

---

## Riding Over Obstacles

Before operating in a new area, check for obstacles. Watch out for bumps, rain ruts, potholes and other obstacles in the terrain. When you approach any obstacle, reduce your speed and be prepared to stop. Never try to ride over large obstacles, such as large rocks or fallen logs.

### **WARNING**

Improperly operating over obstacles could cause loss of control or a collision and could cause the ATV to overturn.

When you go over obstacles, always follow proper procedures as described in this owner's manual.

# Riding Your ATV

---

## Riding Through Water

Your ATV is designed to travel through water up to approximately 10 inches deep. Before crossing a stream, make sure the water is not too deep or flowing too fast.

### **WARNING**

The ATV tyres have some ability to float. Operating this ATV through deep or fast-flowing water may cause a loss of traction and loss of control, which could lead to an accident.

Never operate this ATV in fast-flowing water or in water deeper than that specified in this Owner's Manual.

1. Choose a path where both banks have gradual slopes.
2. Proceed through the water at a slow, steady speed.
3. Watch out for submerged obstacles and slippery rocks.
4. Avoid getting the spark plug or air cleaner wet, as this would cause the engine to stop.
5. After leaving the water, always test both the front and rear brakes.
  - Riding through water can make the brakes less effective than normal, and may reduce stopping ability.
  - If necessary, apply the brakes repeatedly until they dry out and operate normally.
  - If the brakes don't regain effectiveness, stop your ATV and follow the procedures on page 158 .

# Parking

---



1. Look for level parking area. Make sure the ground surface is firm.
2. After bringing your ATV to a stop, hold the brakes while you shift into neutral.
3. Set the parking brake.
4. Turn the ignition switch OFF ( ○ ).
5. If you're through riding for the day, turn the fuel valve OFF.

If it is necessary to start the engine when your ATV is stopped on a grade in gear, rock the vehicle back and forth to allow shifting the transmission into neutral.

## Parking on a Steep Incline or a Loose or Slippery Surface

If you must park your ATV on a steep incline or loose or slippery surface, use the following procedure:

1. While holding the brakes, set the parking brake.
2. Turn the ignition switch OFF ( ○ ) and release the brakes.
3. If the ATV begins to move, either while sitting on it or after you dismount, find a better parking location.
4. If rocks or other objects are available, you can block the wheels as shown for additional security.



# Servicing Your Honda

---

To help keep your ATV in good shape, this section includes a Maintenance Schedule for required service and step-by-step instructions for specific maintenance tasks. You'll also find important safety precautions, information on fuels and oils, and tips for keeping your Honda looking good.

For information about replacing the fuse, see page 164 .

## *Before You Service Your Honda*

The Importance of Maintenance .....	73
Maintenance Safety .....	74
Important Safety Precautions .....	75
Maintenance Schedule .....	76
Maintenance Record .....	80

## *Service Preparations*

Component Locations .....	81
Tool Kit .....	84
Owner's Manual Storage .....	85
Seat Removal .....	86

(cont'd)

# Servicing Your Honda

---

## *Service Procedures*

### Fluids & Filters

Fuel .....	87
Engine Oil .....	90
Gear Case Oil .....	96
Air Cleaner .....	98

### Engine

Throttle.....	103
Carburetor Choke Cable & Knob.....	105
Clutch System .....	106
Engine Idle Speed and Air-Fuel Mixture .....	108
Spark Plug .....	110
Valves.....	113
Spark Arrester .....	114

### Chassis

Brakes.....	116
Tyres .....	126
Engine Guard & Skid Plates.....	133

### Electrical

Battery .....	134
---------------	-----

Appearance Care .....	139
-----------------------	-----

# The Importance of Maintenance

---

A well-maintained ATV is essential for safe, economical, and trouble-free riding. It will also help reduce air pollution. Careful pre-ride inspections and good maintenance are especially important because your ATV is designed to be ridden over rough off-road terrain.

To help you properly care for your ATV, this section of the manual provides a Maintenance Schedule. The service intervals in this schedule are based on average riding conditions.

More frequent service is needed if you subject your ATV to severe use or ride in unusually wet or dusty areas.

## **WARNING**

Improperly maintaining this ATV or failing to correct a problem before you ride can cause a crash in which you can be seriously hurt or killed.

Always follow the inspection and maintenance recommendations and schedules in this owner's manual.

Frequent servicing of the air cleaner is especially important to help you avoid a possible costly engine repair.

If your ATV overturns or is involved in a crash, be sure your Honda dealer inspects all major parts, even if you are able to make some repairs.

# Maintenance Safety

---

This section includes instructions on how to perform some important maintenance tasks. If you have basic mechanical skills, you can perform many of these tasks with the tools provided with your ATV.

Other tasks that are more difficult and require special tools are best performed by professionals. Removing the wheels should normally be handled only by a Honda technician or other qualified mechanic. Instructions are included in this manual only to assist in emergency service.

Some of the most important safety precautions follow. However, we cannot warn you of every conceivable hazard that can arise in performing maintenance. Only you can decide whether or not you should perform a given task.

## **WARNING**

Failure to properly follow maintenance instructions and precautions can cause you to be seriously hurt or killed.

Always follow the procedures and precautions in this owner's manual.



# Maintenance Safety

---

## Important Safety Precautions

- Make sure the engine is off before you begin any maintenance or repairs. This will help eliminate several potential hazards:  
**Carbon monoxide poisoning from engine exhaust.** Be sure there is adequate ventilation whenever you operate the engine.  
**Burns from hot ATV parts.** Let the engine and exhaust system cool before touching.  
**Injury from moving parts.** Do not run the engine unless instructed to do so.
- Read the instructions before you begin, and make sure you have the tools and skills required.
- To reduce the possibility of a fire or explosion, be careful when working around petrol. Use only non-flammable solvent, not petrol, to clean parts. Keep cigarettes, sparks, and flames away from all fuel-related parts.

Remember that your Honda dealer knows your ATV best and is fully equipped to maintain and repair it. To ensure the best quality and reliability, use only new genuine Honda parts or other equivalents for repair and replacement. If you have the tools and skills required for additional maintenance jobs, you can purchase an official Honda Shop Manual.

# Maintenance Schedule

---

The required Maintenance Schedule that follows specifies how often you should have your ATV serviced, and what things need attention. It is essential to have your ATV serviced as scheduled to maintain safe, dependable performance and proper emission control.

The service intervals in this Maintenance Schedule are based on average riding conditions. Some items will need more frequent service if you ride in unusually wet or dusty areas or at full throttle. Consult your *Honda dealer for recommendations applicable to your individual needs and use.*

Some items in the Maintenance Schedule can be performed with basic mechanical skills and hand tools. Procedures for these items are provided in this manual. Other items involve more extensive procedures and may require special training, tools, and equipment. We recommend that you have your Honda dealer perform these tasks unless you have advanced mechanical skills and the required tools and equipment. Procedures for such items in this schedule are provided in an official Honda Shop Manual available for purchase.

If you do not feel capable of performing a given task or need assistance, remember that your Honda dealer knows your ATV best and is fully equipped to maintain and repair it. If you decide to do your own maintenance, use only genuine Honda parts or their equivalents for repair or replacement to ensure the best quality and reliability.

# Maintenance Schedule

---

Perform the pre-ride inspection (page 31 ) and owner maintenance on this section at each scheduled maintenance period.

Each item on the maintenance schedule requires some mechanical knowledge. Certain items (particularly those marked \* and \*\*) may require more technical information and tools. Consult your Honda dealer.

- \* Should be serviced by your Honda dealer, unless you have the proper tools and service data and are mechanically qualified. Refer to the official Honda Shop Manual.
- \*\* In the interest of safety, we recommend these items be serviced only by your Honda dealer.

## *Summary of Maintenance Schedule Notes & Procedures:*

### NOTES:

1. Service more frequently when riding in dusty areas, sand or snow.
2. Service more frequently after riding in very wet or muddy conditions.
3. Replace every 2 years. Replacement requires mechanical skill.

# Maintenance Schedule

## Maintenance Procedures:

I: inspect and clean, adjust, lubricate, or replace, if necessary

C: clean

A: adjust

L: lubricate

R: replace

ITEMS		FREQUENCY	WHICHEVER COMES FIRST ⇔ NOTE	km mi HOURS	INITIAL MAINT. 150 100 20	REGULAR MAINT. INTERVAL			Refer to page
						1000	2000		
						600	1200		
						100	200		
*	FUEL LINE						I		—
*	THROTTLE OPERATION						I		103
*	CARBURETOR CHOKE						I		105
	AIR CLEANER	NOTE 1				C	C		98
	AIR CLEANER HOUSING DRAIN TUBE	NOTE 2				I	I		102
	SPARK PLUG					I	I		110
*	VALVE CLEARANCE				I	I	I		113
	ENGINE OIL				R	R	R		90
**	ENGINE OIL STRAINER SCREEN						C		—
**	ENGINE OIL CENTRIFUGAL FILTER						C		—
*	ENGINE IDLE SPEED				I	I	I		108

\* Should be serviced by your Honda dealer, unless you have the proper tools and service data and are mechanically qualified. Refer to the official Honda Shop Manual.

\*\* In the interest of safety, we recommend these items be serviced only by your Honda dealer.

# Maintenance Schedule

ITEMS		FREQUENCY	WHICHEVER COMES FIRST ⇒ NOTE	km mi HOURS	INITIAL MAINT. 150 100 20	REGULAR MAINT. INTERVAL		Refer to page
						1000	2000	
						600	1200	
						100	200	
	REAR FINAL GEAR CASE OIL					(REVERY 2 YEARS)		96
*	BRAKE FLUID	NOTE 3						117
*	BRAKE SHOE WEAR	NOTE 1						124
*	BRAKE PAD WEAR	NOTE 1,2						119
	BRAKE SYSTEM							116
*	REVERSE LOCK SYSTEM							107
	SKID PLATES, ENGINE GUARD							133
*	CLUTCH SYSTEM							106
*	SUSPENSION							—
*	SPARK ARRESTER					C	C	114
*	NUTS, BOLTS, FASTENERS							—
**	WHEELS/TYRES							—
**	STEERING SHAFT HOLDER BEARINGS							—
**	STEERING SYSTEM							—

\* Should be serviced by your Honda dealer, unless you have the proper tools and service data and are mechanically qualified. Refer to the official Honda Shop Manual.

\*\* In the interest of safety, we recommend these items be serviced only by your Honda dealer.

# Maintenance Record


---

Keeping an accurate maintenance record will help ensure that your ATV is properly maintained. Retain detailed receipts to verify the maintenance was performed. If the ATV is sold, these receipts should be transferred with the ATV to the new owner. Make sure whoever performs the maintenance completes this record. All scheduled maintenance, including the 150 km (100 mile) or 20 hours initial maintenance, is considered a normal owner operating cost and will be charged for by your dealer. Use the space under Notes to record anything you want to remind yourself about or mention to your dealer.

km (Miles) or hours	Date	Performed By:	Notes
150 (100) or 20			
1,000 (600) or 100			
2,000 (1,200) or 200			
3,000 (1,800) or 300			
4,000 (2,400) or 400			
5,000 (3,000) or 500			
6,000 (3,600) or 600			
7,000 (4,200) or 700			
8,000 (4,800) or 800			


# Component Locations

---



# Component Locations


---





# Component Locations

---



# Tool Kit

---


The tool kit ( 1 ) is stored in the storage compartment under the seat.

The tools in the kit are sufficient to perform routine maintenance and simple repairs. Any extensive work requiring additional tools should be performed by your Honda dealer.

The tool kit includes the following items:

- \* standard/Phillips screwdriver
- \* screwdriver handle
- \* air pressure gauge
- \* spark plug wrench
- \* tool case

## UNDER THE SEAT



(1) tool kit

# Owner's Manual Storage


Your ATV provides storage for the owner's manual so you'll have it with you for easy reference. Store your owner's manual (1) in the storage compartment (2) under the seat.

The storage box (3) is stored in the storage compartment. The storage box contains the owner's manual and tool kit (4) (including the air pressure gauge).

The owner's manual and spare fuse (5) should be stored in the plastic document bag (6). The storage box should be stored in the storage compartment.

Be careful not to flood this area when washing your ATV.

## UNDER THE SEAT



- (1) owner's manual
- (2) storage compartment
- (3) storage box


- (4) tool kit
- (5) spare fuse
- (6) plastic document bag

# Seat Removal

---

Refer to *Safety Precautions* on page 75 .

The seat must be removed for the air cleaner, battery and fuse maintenance.



(1) seat lock lever

(2) seat

(3) front prongs

(4) hooks

(5) studs

## Removal

1. Pull the seat lock lever ( 1 ) at the right side of the seat.
2. Slide the seat ( 2 ) back and lift it.

## Installation

1. Insert the front prongs ( 3 ) into the hooks ( 4 ) on the frame and press the studs ( 5 ) into the grommets on the frame.
2. Press down on the seat until locks.

Refer to *Safety Precautions* on page 75 .

## Fuel Recommendation

type	unleaded
pump octane number	86 (or higher)

We recommend that you use unleaded fuel because it produces fewer engine deposits and extends the life of exhaust system components.

Your engine is designed to use any petrol that has a pump octane number of 86 or higher. Petrol pumps at service stations normally display the pump octane number. For information on the use of *petrol containing alcohol*, see page 178 .

Use of lower octane petrol can cause persistent “pinging” or “spark knock” (a loud rapping noise) which, if severe, can lead to engine damage. Light pinging experienced while operating under a heavy load, such as climbing a hill, is no cause for concern.

If pinging or spark knock occurs at a steady engine speed under normal load, change brands of petrol. If pinging or spark knock persists, consult your Honda dealer.

Never use stale or contaminated petrol or an oil/petrol mixture. Avoid getting dirt, dust, or water in the fuel tank.

# Fuel

## Fuel Capacity

Fuel tank capacity, including reserve:

10.2 ℓ (2.69 US gal , 2.24 Imp gal)


Reserve capacity:

2.5 ℓ (0.66 US gal , 0.55 Imp gal)


The tank should be refilled as soon as possible after switching to reserve, and the fuel valve should be returned to the ON position after refueling to avoid running out of fuel with no reserve.

## Refueling Procedure

Refer to *Safety Precautions* on page 75.



- (1) fuel fill cap
- (2) breather tube



- (3) handlebar cover hole
- (4) filler neck

1. To open the fuel fill cap ( 1 ), turn it counterclockwise.
2. Pull the breather tube ( 2 ) out of the handlebar cover hole ( 3 ).
3. Add fuel until the level reaches the bottom of the filler neck ( 4 ).  
Avoid over filling the tank. There should be no fuel in the filler neck.

## **WARNING**

Petrol is highly flammable and explosive. You can be burned or seriously injured when handling fuel.

- Stop the engine and keep heat, sparks and flame away.
- Handle fuel only outdoors.
- Wipe up spills immediately.

4. After refueling, turn the fuel fill cap clockwise until it clicks.
5. Insert the breather tube ( 2 ) into the handlebar cover hole ( 3 ).
6. If the fuel valve was set to RES, turn the fuel valve ON.

If you replace the fuel fill cap, use only a genuine Honda replacement part.

# Engine Oil

---

Engine oil quality is a major factor that affects both the performance and the service life of the engine.

Using the proper oil (page 91 ) and filter, and regularly checking, adding, and changing oil will help extend your engine's life. Even the best oil wears out. Changing oil helps get rid of dirt and deposits in the engine. Operating the engine with old or dirty oil can damage your engine. Running the engine with insufficient oil can cause serious damage to the engine and transmission.

Change the engine oil as specified in the maintenance schedule on page 78 . When running in very dusty conditions, oil changes should be performed more frequently than specified in the maintenance schedule.



## Oil Recommendation

API classification *	SE,SF or SG
viscosity (weight)	SAE 10W-40
suggested oil	Honda 4-stroke oil or an equivalent.


- \* Motor oils intended for Service SE, SF or SG will show this designation on the container.
- Your ATV does not need oil additives. Use the recommended oil.
  - Do not use oils with graphite or molybdenum additives. They may adversely affect clutch operation.
  - Do not use non-detergent, vegetable, or castor based racing oils.

(cont'd)

# Engine Oil

---

Other viscosities shown in the following chart may be used when the average temperature in your riding area is within the indicated range.



## Checking & Adding Oil

Refer to *Safety Precautions* on page 75 .


Check the engine oil level each day before operating your ATV and add if needed.

1. Park your ATV on a firm, level surface.
2. Start the engine in a well-ventilated area and let it idle for 3 – 5 minutes. Stop the engine and wait 2 – 3 minutes.
3. Remove the oil filler cap/dipstick ( 1 ) from the front crankcase cover and wipe it clean.
4. Insert the dipstick without screwing it in, then remove the dipstick and check the oil level. The oil level should be between the upper level mark ( 2 ) and the lower level mark ( 3 ) on the dipstick.
5. If required, add the specified oil into the filler cap hole, up to the upper level mark on the dipstick. Do not overfill.
6. Reinstall the oil filler cap/dipstick.

### NOTICE

*Running the engine with improper oil level can cause serious engine damage.*

#### LEFT SIDE



(1) dipstick

(2) upper level mark

(3) lower level mark

# Engine Oil

---

## Changing Engine Oil

Refer to *Safety Precautions* on page 75 .

### NOTICE


*Using the wrong oil filter may result in leaks or premature engine damage.*

This procedure requires mechanical skill and professional tools such as a torque wrench, as well as a means for disposing of the drained fluid (page 154 ). If you do not have the skills or the tools, see your Honda dealer.

#### *Drain the Engine Oil:*

1. With the ATV on the level ground, remove the oil filler cap/dipstick from the right crankcase cover.
2. Place an oil drain pan under the crankcase and remove the oil drain plug (1).

#### UNDER ENGINE



(1) oil drain plug

3. Pour the drained oil into a suitable container and dispose of it in an approved manner (page 154 ).

## NOTICE

*Improper disposal of drained fluids is harmful to the environment.*

### *Add Engine Oil:*

1. Check that the drain plug sealing washer is in good condition. If necessary, replace the sealing washer.
2. Reinstall the oil drain plug and tighten it to the specified torque:  
25 N·m (2.5 kgf·m , 18 lbf·ft)
3. Fill the crankcase with the recommended grade oil approximately:  
1.6 l (1.7 US qt , 1.4 Imp qt)
4. Reinstall the oil filler cap/dipstick.
5. Start the engine and let it idle for a few minutes.
6. Stop the engine and check the oil level. Make sure the oil is between the upper and lower level marks on the dipstick. If necessary, add more oil but do not overfill.
7. Check that there are no oil leaks.

If a torque wrench is not used for installation, see your Honda dealer as soon as possible to verify proper assembly.

# Gear Case Oil

---

## Oil Recommendation

type	hypoid gear oil
viscosity (weight)	SAE 80

## Changing Oil


Refer to *Safety Precautions* on page 75.

Changing the oil with the gear case at normal operating temperature to assure complete and rapid draining.

# Gear Case Oil

1. Park the ATV on level ground.
2. Place an oil drain pan under the oil drain plug (1).
3. Remove the oil filler cap (2) and the drain plug.
4. After the oil has completely drained, reinstall the drain plug and tighten it to the specified torque:  
**12 N·m (1.2 kgf·m , 9 lbf·ft)**
5. Fill the gear case with the recommended oil.  
**100 cm<sup>3</sup> (3.4 US oz , 3.5 Imp oz)**
6. Remove the oil level check bolt (3). Make sure the oil level reaches the oil level check hole (4).
7. Install the oil filler cap.

## REAR



(1) oil drain plug  
(2) oil filler cap

(3) oil level check bolt  
(4) oil level check hole

# Air Cleaner

---

Refer to *Safety Precautions* on page 75 .

Proper air cleaner maintenance is very important for off-road vehicles. A dirty, water-soaked, worn-out, or defective air cleaner will allow dirt, dust, mud, and other impurities to pass into the engine.

Service the air cleaner more frequently if you ride in unusually wet or dusty areas. Your Honda dealer can help you determine the correct service interval for your riding conditions.

Your ATV's air cleaner has very specific performance requirements. Use a new genuine Honda air cleaner specified for your model or an air cleaner of equal quality.

## NOTICE

*Using the wrong air cleaner may result in premature engine damage.*

Proper air cleaner maintenance can prevent premature engine wear or damage, expensive repairs, low engine power, poor gas mileage, and spark plug fouling.

## NOTICE


*Improper or lack of proper air cleaner maintenance can cause poor performance and premature engine wear.*



## Cleaning

1. Remove the seat (page 86 ).
2. Uncover the rubber sheet ( 1 ) from the retainer clips ( 2 ).
3. Unlatch the four retainer clips ( 2 ).
4. Remove the air cleaner housing cover ( 3 ).

### UNDER SEAT



(1) rubber sheet  
(2) retainer clips

(3) air cleaner housing cover


(cont'd)

# Air Cleaner

---

5. Loosen the screws (4) and remove the air cleaner assembly (5) from the air cleaner housing.
6. Unscrew the clamp (6).
7. Remove the air cleaner (7) from the air cleaner body (8).
8. Gently wash the air cleaner in clean, non-flammable (high flash point) solvent such as kerosene — not petrol. After cleaning, gently squeeze out the remaining solvent. Avoid twisting or wringing the air cleaner. This can tear the foam.
9. Inspect for tears or cracks in the foam or seams of the air cleaner. Replace the air cleaner if it is damaged.
10. Allow the air cleaner to dry thoroughly before applying oil. A wet air cleaner will not fully absorb the oil.
11. Pour clean air filter oil over the entire surface of the air cleaner. Use both hands to evenly spread the oil into the air cleaner. Gently squeeze out any excess oil. (To keep your hands dry, place the air cleaner in a clean plastic bag before spreading the oil into the air cleaner.)

## UNDER SEAT



(4) screws

(5) air cleaner assembly

(6) clamp

(7) air cleaner


(8) air cleaner body

# Air Cleaner

12. Install the air cleaner on the air cleaner body.
13. Apply a thin coat of grease to the sealing surface of the air cleaner assembly.
14. Install the clamp.
15. Insert the air cleaner assembly into the air cleaner housing.
16. Fasten the screws.

## Dust Cover

### UNDER SEAT



(1) dust cover

(2) air cleaner housing

*Do not push the dust cover ( 1 ) too far into the air cleaner housing ( 2 ).  
If the dust cover is dirty, clean it.*


# Air Cleaner

---

## Air Cleaner Housing Drain Tube

The air cleaner housing drain tube should be serviced in accordance with the Maintenance Schedule. (Riding through water may require more frequent inspection.) If deposits can be seen in the drain tube, the tube must be cleaned before starting the vehicle.

### REAR



(1) drain tube  
(2) clip


(3) air cleaner housing

1. Remove the drain tube (1) by removing the clip (2) under the air cleaner housing (3).
2. Drain the deposits.
3. Reinstall the drain tube, securing it with the clip.

## Throttle Freeplay

Refer to *Safety Precautions* on page 75.

### RIGHT HANDLEBAR



### Inspection

Check freeplay at the throttle lever (1).

Freeplay:

3–8 mm (0.1–0.3 in)

### Adjustment

1. Slide the rubber sleeve (2) back to expose the throttle cable adjuster (3).
2. Loosen the lock nut (4).
3. Turn the adjuster to obtain the correct freeplay.
4. Tighten the lock nut and reinstall the sleeve.
5. After adjustment, check for smooth operation of the throttle lever from fully closed to fully open in all steering positions.

# Throttle

---

## Throttle Inspection

Refer to *Safety Precautions* on page 75 .


1. Check that the throttle assembly is positioned properly and the securing bolts are tight.
2. Check for smooth operation of the throttle lever from fully open to fully closed in all steering positions. If there is a problem, see your Honda dealer.
3. Inspect the condition of the throttle cables from the throttle lever down to the carburetor. If the cable is kinked or chafed, have it replaced.
4. Check the cables for tension or stress in all steering positions.
5. Lubricate the cables with a commercially-available cable lubricant to prevent premature wear and corrosion.

# Carburetor Choke Cable & Knob

---

Refer to *Safety Precautions* on page 75 .

## LEFT HANDLEBAR



(1) choke cable

(2) choke knob

1. Check the condition of the choke cable (1 ).
2. Check the operation of the choke knob (2 ).

If the cable is damaged or kinked, have it replaced by your Honda dealer.


# Clutch System

Your ATV's shift-activated, wet, multiplate clutch is part of the primary drive system. Proper adjustment allows a smooth, gradual engagement when shifting gears.

## Clutch Adjustment

Refer to *Safety Precautions* on page 75.

FRONT



(1) lock nut

(2) clutch adjuster

1. Make sure the ignition switch is OFF (  $\bigcirc$  ).
2. Loosen the lock nut ( 1 ).
3. Turn the clutch adjuster ( 2 ) counterclockwise until you feel slight resistance.
4. Turn the adjuster 1/4 turn clockwise, then tighten the lock nut to hold the adjuster in this position.
5. After adjustment, start the engine and test ride your ATV to be sure the clutch is operating properly.


If you cannot get proper adjustment, or the clutch does not work properly, the cable or clutch friction discs may be worn. See your Honda dealer or refer to official Honda Shop Manual.



## Reverse Lock System Adjustment

Refer to *Safety Precautions* on page 75 .

### LEFT HANDLEBAR



(1) reverse assist lever  
(2) rear brake lever

(3) lock nut  
(4) adjusting nut

1. Check the reverse assist lever ( 1 ) freeplay, measured at the rear brake lever ( 2 ) end near the cable:  
2-4 mm (0.1-0.2 in)
2. To adjust, loosen the lock nut ( 3 ) and turn the adjusting nut ( 4 ).  
After adjustment, tighten the lock nut securely.

### Other Checks

Check the reverse assist lever and cable for loose connections or other damage. If the cable is worn or kinked, have it replaced by your Honda dealer.

# Engine Idle Speed and Air-Fuel Mixture

---

The best way to assure proper carburetion is to see your Honda dealer for regularly scheduled servicing, including carburetor adjustment.

Remember, idle speed adjustment is not a “cure-all” for other problems in your engine’s fuel-delivery system. Adjusting the idle will not compensate for a fault elsewhere.


The engine must be at normal operating temperature for accurate idle speed adjustment.

For information about high altitude carburetor adjustment, see page 177.

## Idle Speed Adjustment

Refer to *Safety Precautions* on page 75.

### RIGHT SIDE



(1) throttle stop screw

(2) pilot screw

1. If the engine is cold, start it and warm it up with ten minutes of stop-and-go riding. Stop the engine.

# Engine Idle Speed and Air-Fuel Mixture

---

2. Park your ATV on a firm, level surface.
3. Connect a tachometer to the engine.
4. Shift into neutral. Start the engine.
5. Adjust idle speed by turning the throttle stop screw ( 1 ).

Idle speed (in neutral):

$1,400 \pm 100 \text{ min}^{-1}(\text{rpm})$

## Air-Fuel Mixture Adjustment

1. Turn the pilot screw ( 2 ) clockwise until you hear the engine miss or decrease in speed.
2. Then turn the screw counterclockwise until the engine misses or decreases in speed again.
3. Centre the pilot screw exactly between the two extreme positions.  
Usually, the correct setting (between extremes of rich and lean) will be found at 1-7/8 turns open from a fully closed position.
4. If idle speed changes after adjusting the fuel mixture, readjust the throttle stop screw.

# Spark Plug

---

## Spark Plug Recommendation

standard spark plug	DPR8EA-9 (NGK) or X24EPR-U9 (DENSO)
for cold climate (below 5°C, 41°F)	DPR7EA-9 (NGK) or X22EPR-U9 (DENSO)

Use only the recommended type of spark plug in the recommended heat range.

### NOTICE

*Using spark plugs with an improper heat range can cause engine damage.*

## Spark Plug Replacement & Inspection


Refer to *Safety Precautions* on page 75 .

1. Clean any dirt from around the spark plug base.
2. Disconnect the spark plug cap. Take care to avoid damaging the spark plug wire when disconnecting the cap.
3. Using the spark plug wrench provided in the tool kit, remove the spark plug.

# Spark Plug

4. Inspect the electrodes and centre porcelain for deposits, corrosion, or carbon fouling. If the corrosion or deposits are heavy, replace the plug. Clean a carbon or wet-fouled plug with a plug cleaner, if available, or a wire brush. Inspect the spark plug electrodes for wear. The centre electrode (1) should have a flat tip and sharp edges, and the side electrode (2) should not be eroded. If the electrodes and insulator tip appear unusually fouled or burned, we suggest that you contact your Honda dealer.
  5. Discard the spark plug if there is apparent wear or if the insulator is cracked or chipped.
  6. Using a wire-type feeler gauge, check the spark plug gap (3). If adjustment is necessary, bend the side electrode carefully.
- The gap should be:

**0.8—0.9 mm (0.03—0.04 in)**



- (1) centre electrode  
(2) side electrode  
(3) spark plug gap

(cont'd)

# Spark Plug

---

7. With the plug washer attached, thread the spark plug in by hand to prevent cross-threading.

Tighten the spark plug:

- about 1/8 – 1/4 turn after it seats (if the old plug is good).
- about 1/2 turn after it seats (if installing a new plug).

## NOTICE

*Improperly tightened spark plug can damage the engine. If a plug is too loose, a piston may be damaged. If a plug is too tight, the threads may be damaged.*

## Valve Inspection

Refer to *Safety Precautions* on page 75 .

Valve clearance should be:

0.13 mm (0.005 in)

Excessive clearance will cause noise. Insufficient clearance will cause loss of power and possibly damage the valves.

For those who are mechanically proficient and have the proper tools, instructions on adjusting valve clearances are given in the official Honda Shop Manual. All others should have valves adjusted by your Honda dealer.

# Spark Arrester

---

Refer to *Safety Precautions* on page 75.


The spark arrester must be serviced every 100 operating hours to maintain its efficiency.

The exhaust system must be periodically purged of accumulated carbon. To purge the system:

The use of safety glasses is recommended for this procedure.

Because of the possible fire hazard, check that there are no combustible materials in the area before purging the spark arrester.

REAR



(1) bolts

(2) spark arrester

(3) gasket

(4) muffler


1. Select a well-ventilated area free of combustible materials and make sure the exhaust pipe is cool.
2. Remove the three bolts (1), the spark arrester (2), and the gasket (3) from the muffler (4).



# Spark Arrester

---

3. Use a brush to remove carbon deposits from the spark arrester (5) screen. Be careful to avoid damaging the spark arrester screen. The spark arrester must be free of breaks and holes. Replace, if necessary. Check the gasket. Replace, if necessary.



(5) spark arrester

4. Install the spark arrester and the gasket in the muffler and tighten the three bolts securely.

# Brakes

---

The hydraulic disc brakes (front) and single mechanical drum brake (rear) on your ATV dissipate heat generated by the friction of the brake pads on the disc (front) and the brake shoes on the drums (rear) as the wheels are slowed.

## Hydraulic Front Brake

As the front brake shoes wear, brake fluid level will drop. A leak in the system will also cause the level to drop.

There are no adjustments to perform, but fluid level and pad wear must be inspected periodically. The system must be inspected frequently to ensure there are no fluid leaks.

If the brake lever or brake pedal freeplay does not feel within the normal range while riding, check the brake pads for wear (page 117). Worn pads should be replaced. If the pads are not worn beyond the recommended limit, there is probably air in the brake system. See your Honda dealer to have the air bled from the system.

## Drum Rear Brake

For more information, see page 120.

## **Brake Fluid Recommendation**


brake fluid	DOT 4 Brake Fluid
-------------	-------------------

The recommended brake fluid is DOT 4 Brake Fluid, or any brake fluid of equal quality and performance. Use fresh brake fluid from a sealed container. Be sure to read the label before opening the sealed container. An opened container may be contaminated or may have absorbed moisture from the air.

## Fluid Level Inspection

Refer to *Safety Precautions* on page 75 .

### RIGHT HANDLEBAR



(1) LOWER level mark

If your inspection indicates a low fluid level, have your Honda dealer add the recommended fluid.

Do not add or replace brake fluid, except in an emergency. If you do add fluid, have your Honda dealer check the system as soon as possible.

### NOTICE

*Brake fluid can damage plastic and painted surfaces. Handle with care.*

# Brakes

---

Wipe up spills immediately. Avoid contact with skin or eyes. In case of contact, wash thoroughly and call a doctor immediately if it contacts your eyes.

## Other Inspections


- Make sure there are no fluid leaks.
- Check for deterioration or cracks in the hoses and fittings. If the hoses are worn or cracked, have them replaced by your Honda dealer.

## Brake Pad Wear

Refer to *Safety Precautions* on page 75 .

Brake pad wear will depend upon the severity of usage and riding conditions. The pads will wear faster in wet or muddy conditions. Inspect the pads visually during all regular service intervals to determine the pad wear.

RIGHT FRONT (Left side similar)



(1) wear indicator

(2) edge of reference mark

Check the wear indicator ( 1 ). If the wear indicator aligns with the edge of the reference mark ( 2 ), both pads must be replaced, see your Honda dealer for this replacement.


Always inspect both pads in both the right and left front brake calipers.

# Brakes

---

## Rear Brake Pedal Freeplay

RIGHT SIDE



(1) rear brake pedal

### Inspection


Measure the distance the rear brake pedal (1) moves before the brake starts to take hold. Freeplay, measurement at the tip of the end of the pedal, should be:

15 - 20 mm (0.6 - 0.8 in)

If necessary, adjust to the specified range.

## Adjustment

### LEFT REAR



(2) brake pedal adjusting nut


(3) brake arm pin

Turn the brake pedal adjusting nut (2 ), located on the brake operating rod at the rear of the frame. Make sure the cutout on the adjusting nut is properly seated on the brake arm pin (3 ).

# Brakes

---

## Rear Brake Lever Freeplay



(1) rear brake lever

### Inspection

Measure the distance the rear brake lever (1) moves before the brake starts to take hold. Freeplay, measurement at the tip of the end of the brake lever, should be:


15-20 mm (0.6-0.8 in)

If necessary, adjust to the specified range.



## Adjustment

### LEFT REAR



(2) brake lever adjusting nut

(3) brake arm pin

Turn the brake lever adjusting nut (2), located on the brake operating rod at the rear of the frame. Make sure the cutout on the adjusting nut is properly seated on the brake arm pin (3).

### **Other Inspection**

- Check that the brake lever and brake pedal assemblies are positioned properly and the securing bolts are tight.
- Make sure that the brake cables, brake arm, spring, and fasteners are in good condition.

# Brakes


---

## Brake Shoe Wear

Refer to *Safety Precautions* on page 75 .

The rear brake is equipped with an external brake wear indicator that lets you check brake wear without disassembly. Application of the brake control causes the arrow on the brake arm to move toward a reference mark on the brake panel.

### LEFT REAR



(1) arrow


(2) brake arm

(3) reference mark

1. Apply the brake control and check the movement of the arrow ( 1 ) on the brake arm ( 2 ).
2. Replace the brake shoe if the arrow aligns with the reference mark ( 3 ) on the brake panel upon full application of the brake. If replacement is necessary, see your Honda dealer.

## Draining Water from Brakes

Refer to *Safety Precautions* on page 75 .



(1) rear brake drain bolt

1. Make sure the engine is off and the parking brake is set.
2. Remove the rear brake drain bolt ( 1 ) from the bottom of the rear brake cover.

If any water drains, the brake seals must be replaced by your Honda dealer as soon as possible.

# Tyres

---

To safely operate your ATV, your tyres must be the proper type and size, in good condition with adequate tread, and correctly inflated.

## **WARNING**

Using tyres that are excessively worn or improperly inflated can cause a crash in which you can be seriously hurt or killed.

Follow all instructions in this owner's manual regarding tyre inflation and maintenance.

This ATV is equipped with low pressure tubeless tyres. Although the tyres are designed specifically for off-road use, they are not immune to punctures. Always select your riding area with care.

The following pages give detailed information on how and when to check your air pressure, how to inspect your tyres for wear and damage, and our recommendations for tyre repair and replacement.

## Air Pressure

Refer to *Safety Precautions* on page 75 .

Properly inflated tyres provide the best combination of handling, tread life, and riding comfort. Generally, underinflated tyres wear unevenly, adversely affect handling, and are more likely to fail from being overheated. Overinflated tyres make your ATV ride more harshly, are more prone to damage from surface hazards, and wear unevenly.

Make sure the valve stem caps are secure. If necessary, install a new cap.

# Tyres

---

Always check air pressure when your tyres are “cold.” If you check air pressure when your tyres are “warm” — even if your ATV has only been ridden for a few miles — the readings will be higher. If you let air out of warm tyres to match the recommended cold tyre pressures, the tyres will be underinflated. Be sure to check tyre pressure at the riding site, since changes in altitude can affect air pressure.

The recommended “cold” tyre pressures are:

		FRONT	REAR
NO CARGO	RECOMMENDED PRESSURE	30 kPa (0.30 kgf/cm <sup>2</sup> , 4.4 psi)	20 kPa (0.20 kgf/cm <sup>2</sup> , 2.9 psi)
	MAXIMUM PRESSURE	34 kPa (0.34 kgf/cm <sup>2</sup> , 5.0 psi)	23 kPa (0.23 kgf/cm <sup>2</sup> , 3.3 psi)
	MINIMUM PRESSURE	26 kPa (0.26 kgf/cm <sup>2</sup> , 3.8 psi)	17 kPa (0.17 kgf/cm <sup>2</sup> , 2.5 psi)

A manually operated tyre pump should be used rather than the high pressure system found in service stations. This will minimize the possibility of tyre damage from overinflation. If you use a high pressure system at a service station, add air in small amounts and check the pressure increase frequently to prevent possible tyre damage from overinflation.

## **WARNING**

Operating this ATV with improper tyres, or with uneven tyre pressure may cause loss of control, and you could be seriously injured or killed.

- Always use the size and type tyres specified in this owner's manual for this vehicle.
- Always maintain proper tyre pressure as described in this owner's manual.

## **Inspection**

Refer to *Safety Precautions* on page 75.


Whenever you check the tyre pressures, you should also look for:

- Bumps or bulges in the side of the tyre or the tread. Replace any tyre that has a bump or bulge.
- Cuts, slits, or cracks in the tyres. Replace the tyre if you can see fabric or cord.
- Nails or other foreign objects embedded in the side of the tyre or tread.
- Excessive tread wear.

# Tyres

Also, if you hit a pothole or other hard object while riding, stop as soon as you safely can and carefully inspect the tyres for damage.

## Tread Wear



To check the condition of a tyre tread, measure the groove depth ( 1 ) in the centre of the tyre, or check the wear indicator ( 2 ).

For best performance, you should replace a tyre before the tread depth at the centre reaches the following limits:

front	4 mm (0.16 in)
rear	4 mm (0.16 in)



## **Tyre Repair**

Refer to *Safety Precautions* on page 75 .

A tyre that is repaired, either temporarily or permanently, will have lower speed and performance limits than a new or undamaged tyre.

A temporary repair can sometimes be made in an emergency situation. However, since a temporary repair may not hold, you must ride very slowly, preferably without any cargo, and have the tyre replaced or permanently repaired as soon as possible. (For more information on temporary repairs, see *If You Have a Flat Tyre*, page 161.)

A permanent repair, such as an internal plug patch, can be made if a tyre has only a small puncture in the tread area. However you may not be able to safely carry as much weight. If you choose to have a tyre repaired, be sure the repair work is performed by a professional.

If you have a tyre professionally repaired at a non-Honda facility, we recommend that you have the work checked by your Honda dealer.

# Tyres

---

## Tyre Replacement

Refer to *Safety Precautions* on page 75.

The tyres that came on your ATV were designed to match the performance capabilities of your ATV and provide the best combination of handling, braking, and comfort.

It is best to replace all four tyres, however if that is not possible, you must replace the tyres in pairs (front or rear) with tyres of the same size and type as the originals. Never replace just one tyre.

### **WARNING**

Installing improper tyres on your ATV can affect handling and stability. This can cause a crash in which you can be seriously hurt or killed.

Always use the size and type of tyres recommended in this owner's manual.

The recommended tyres for your ATV are:

front	AT22 × 7-10 ★★	KT171 DUNLOP
rear	AT22 × 10-9 ★	KT175 DUNLOP

When you replace a tyre, remember.


Have the tyre replaced by your Honda dealer if possible.

If you have a tyre professionally replaced at a non-Honda facility, we recommended that you have the work checked by your Honda dealer.

# Engine Guard & Skid Plates

---

Refer to *Safety Precautions* on page 75.



(1) engine guard

(2) skid plates

The engine guard ( 1 ) protects the engine crankcase.

The skid plates ( 2 ) protect the frame and rear final gear case. Check the guard and plates for cracks, damage or looseness at intervals shown in the Maintenance Schedule.

Have the engine guard and skid plates replaced if they are cracked or damaged. If the guard and plate bolts are loose, tighten them securely.

# Battery

---

Your ATV has a maintenance-free type battery. You do not have to check the battery electrolyte level or add distilled water as you would with a conventional-type battery.

## NOTICE

*Your battery is a maintenance-free type and can be permanently damaged if the cap strip is removed.*

Electrical accessories use current from the battery — even when the ignition is OFF. Limited operation also allows the battery to discharge. If you have electrical accessories on your ATV — or do not ride frequently, we recommend that you charge the battery frequently (see *Battery Charging*, page 138 ).

If you do not expect to ride your ATV for at least two weeks, we recommend you remove the battery — or at least disconnect the battery cables (negative cable first).

If you plan to store your ATV, see *Battery Storage*, page 135 .

If your battery seems weak and/or is leaking electrolyte (causing slow starting or other electrical problems), see your Honda dealer.

## Battery Storage

Refer to *Safety Precautions* on page 75.

If you plan to store your ATV, we recommend you remove the battery and store it where it can be charged at least every 30 days to maintain its service life.

If you do not remove the battery, we recommend disconnecting the battery cables (negative cable first).

You will get the best storage results from removing the battery and slow (trickle) charging it every 30 days (see *Battery Charging*, page 138 ).

Before you remove the battery, be sure to read all the information that follows, as well as the information on the battery label.

### **WARNING**

The battery gives off explosive hydrogen gas during normal operation.

A spark or flame can cause the battery to explode with enough force to kill or seriously hurt you.


Wear protective clothing and a face shield, or have a skilled mechanic do the battery maintenance.

# Battery

---

The battery is located in a compartment under the seat.

## UNDER SEAT



(1) battery holder

(2) mount bolts

(3) negative ( - ) terminal lead

(4) battery

(5) positive ( + ) terminal lead

1. Make sure the ignition switch is OFF (  $\bigcirc$  ).
2. Remove the seat (page 86 ).
3. Remove the battery holder ( 1 ) by removing the mount bolts ( 2 ).
4. Disconnect the negative ( - ) terminal lead ( 3 ) from the battery ( 4 ) first, then disconnect the positive ( + ) terminal lead ( 5 ).
5. Remove the battery.

6. Charge the battery (see following section), unless you have been riding regularly.
7. Store your battery in an easy-to-reach location off the floor, in an area protected from freezing temperature and direct sunlight.
8. Clean the battery box after removing the battery for storage. Dry the battery box and, if paint is missing, re-paint the area.
9. Slow charge the battery (see following section) once every 30 days.


## Installation

1. Install in the reverse order of removal.
2. Check all bolts and other fasteners are secure.

# Battery

## Battery Charging

Refer to *Safety Precautions* on page 75.



(1) “trickle” charger

Be sure to read the information that came with your battery charger and follow the instructions on the battery. Improper charging may damage the battery.

We recommend using a “trickle” charger (1) for home charging. These units can be left connected for long periods without risking damage to the battery. However, do not intentionally leave the charger connected longer than the time period recommended in the charger’s instructions.

Avoid using an automotive-type battery charger. An automotive charger can overheat an ATV battery and cause premature damage.



# Appearance Care

---

Frequent cleaning and polishing will keep your Honda looking newer longer.

Frequent cleaning also identifies you as an owner who values his ATV. A clean ATV is also easier to inspect and service.

## General Recommendations

Refer to *Safety Precautions* on page 75.

- To clean your ATV, you may use:
  - water
  - a mild, neutral detergent and water
  - a mild spray and wipe cleaner/polisher
  - a mild spray and rinse cleaner/degreaser and water
- Avoid products that contain harsh detergents or chemical solvents that could damage the metal, paint, and plastic on your ATV.
- If your ATV is still warm from recent operation, give the engine and exhaust system time to cool off.
- Park in a shady area. Washing your ATV in bright sunlight may cause the finish to fade because water droplets intensify the sun's brightness.
- Spotting is also more likely because surface water can dry before you have time to wipe it off.
- Clean your ATV regularly to protect surface finishes.
- We recommend the use of a garden hose to wash your ATV. High pressure washers (like those at coin-operated car washers) can damage certain parts of your ATV.

### NOTICE

*High pressure water (or air) can damage certain parts of your ATV.*

- After cleaning, inspect for damage, wear, and leaks (fuel, oil, coolant and brake fluid).

# Appearance Care

---

## Washing Your ATV with a Mild Detergent

Refer to *Safety Precautions* on page 75.

1. Rinse your ATV thoroughly with cool water to remove loose dirt.
  2. Fill a bucket with cool water. Mix in a mild, neutral detergent, such as dish washing liquid or a product made especially for washing motorcycles or automobiles.
  3. Wash your ATV with a sponge or soft towel. As you wash, check for heavy grime. If necessary, use a mild cleaner/degreaser to remove the grime.
  4. After washing, rinse your ATV thoroughly with plenty of clean water to remove any residue. Detergent residue can corrode alloy parts.
  5. Dry your ATV with a chamois or a soft towel. Leaving water on the surface to air dry can cause dulling and water spots. As you dry, inspect for chips and scratches.
  6. Start the engine and let it idle for several minutes. The engine heat will help dry moist areas.
  7. As a precaution, ride your ATV at a slow speed and apply the brakes several times. This will help dry the brakes and restore normal braking performance.
- If the inside of the headlight lens appears clouded immediately after washing, it should clear after a few minutes of riding.

## Spray Cleaning Your ATV

Refer to *Safety Precautions* on page 75.

Avoid using spray cleaner products on the tyres or suspension components.

Suggestions for using spray cleaner(s) follow:

ATV condition	Recommended Cleaning
Dust and fingerprint smudges.	Apply a spray cleaner/polish and wipe paint, chrome, glass, and clear plastic.
Light road grimes.	Spray any difficult-to-reach or very dirty areas with a spray cleaner/degreaser. Rinse and dry. Apply a spray cleaner/polish and wipe with a non-abrasive cloth.
Heavy grime. Oil leaks. Brake dust.	Use a spray cleaner/degreaser. If necessary, rub with a sponge. Rinse and dry. Apply a spray cleaner/polish and wipe with a non-abrasive cloth.
Dull, corroded chrome or aluminum.	Apply a high quality chrome/aluminum polish and wipe with a non-abrasive cloth.

# Appearance Care

---

## Finishing Touches

Refer to *Safety Precautions* on page 75.

After washing your ATV, consider using a commercially-available spray cleaner/polish or quality liquid or paste wax to finish the job. Use only a non-abrasive polish or wax made specifically for motorcycles or automobiles. Apply the polish or wax according to the instructions on the container.

If a surface on your ATV is chipped or scratched, your Honda dealer has touch-up paint to match your ATV's colour. Be sure to use your ATV's colour code (page 171 ) when you buy touch-up paint.

If the frame has a chip that exposes the metal, first apply primer (to prevent corrosion) and then apply the touch-up paint. Several thin layers of touch-up paint are better than one thick coat.

## **Painted Aluminum Wheel Maintenance**

Refer to *Safety Precautions* on page 75.

Aluminum may corrode from contact with dirt, mud, or road salt. Clean the wheels after riding through any of these substances. Use a wet sponge and mild detergent. Avoid stiff brushes, steel wool, or cleaners containing abrasives or chemical compounds.

After washing, rinse with plenty of water and dry with a clean cloth.

If the paint is chipped, apply touch-up paint.

Here's helpful advice on how to prepare for an off-road adventure, how to transport and store your Honda, and how to be an environmentally responsible ATV owner.

Preparing for a Ride .....	146
What to Take to The Riding Area .....	146
What to Take on The Trail .....	147
Transporting Your Honda .....	148
Storing Your Honda .....	150
You & the Environment.....	154

# Preparing for a Ride

---

A safe and enjoyable ride begins with good planning and preparation. Always ride with at least one other person in case you have trouble, and let someone know where you're going and when you expect to return.

Before riding in an unfamiliar area, find out in advance if you need special permits, get maps so you can study the terrain, and talk to other riders who know the area.

## What to Take to the Riding Area

Along with your ATV and riding gear, you should take along some tools and supplies in case you have a problem. For some of the difficulties you might encounter, see *Taking Care of the Unexpected*, which begins on page 155.

We recommend that you always take water, food, a first aid kit, and your owner's manual. Other items you should consider loading on your truck or trailer include:

- a tool kit
- tyre repair supplies and tools, and tyres
- extra parts, control levers, cables, and spark plugs
- wire, duct tape, and rope
- extra petrol

For safety, all refueling should be done at a gas station on the way to the riding area or at your base camp.

# Preparing for a Ride

---

## What to Take on the Trail

What you take with you during a ride depends on the kind of terrain, how long you expect to ride, how far you might go from your base camp or help, and how experienced you or your companions are in making repairs.

If you decide to take some tools, spare parts, or other supplies on the trail, be sure you can carry them safely and know how to use them. Also, be sure to follow the loading guidelines and weight limit (page 35).



# Transporting Your Honda

---

Do not tow your ATV behind a car or other vehicle.


When you transport your ATV, we recommend that you carry the vehicle in its normal operating position (on all four wheels) and follow these procedures:

1. Set the parking brake and place the transmission in gear.
2. Turn the fuel valve OFF.
3. Secure the vehicle with "tie-down straps" in the areas shown.


Suitable "tie-down straps" are available from your Honda dealer.

Ordinary rope is not recommended because it can stretch under load.

Using tie-down straps in any other areas can damage your ATV.



- (1) front carry pipe  
(2) right footpeg



- (3) left footpeg  
(4) rear carry pipe or  
rear axle shaft

# Transporting Your Honda

---

If it is necessary to incline your ATV upright on the rear end:

1. Follow steps 1 and 2 on the previous page.
2. Place a suitable container under the carburetor drain tube.
3. Turn the drain screw counterclockwise and drain the fuel from the carburetor.
4. After draining the carburetor, turn the drain screw clockwise until it is tight.
5. Pour the drained fuel into the fuel tank.
6. Tilt the vehicle and secure properly.

## **WARNING**

Inclining this ATV without first draining fuel from the carburetor could cause the fuel to explode or ignite.

Always drain fuel from the carburetor before inclining this ATV. Always handle fuel in a well-ventilated area with the engine off. Do not smoke or allow flames or sparks in the area where fuel is handled. If any fuel is spilled, make sure the area is dry before starting the engine.

# Storing Your Honda

---

If you won't be riding for an extended period, such as during the winter, thoroughly inspect your ATV and correct any problem before storing it. That way, needed repairs won't be forgotten and it will be easier to get your ATV running again.

We suggest you perform the following procedures to keep your ATV in top condition. These storage procedures will reduce the deterioration that can occur during storage.

# Storing Your Honda

---

## Preparation for Storage

Refer to *Safety Precautions* on page 75.

This procedure requires a means for draining and disposing of drained fuel (page 154 ).

1. Change the engine oil (page 94 ).
2. Fill the fuel tank. Make sure the fuel fill cap is properly installed.
3. Check that the fuel valve is OFF.
4. Drain the carburetor into an approved petrol container and dispose of it in an approved manner (page 154).

If storage will last longer than one month, carburetor draining is important, to assure proper performance after storage.

### **WARNING**


Petrol is highly flammable and explosive. You can be burned or seriously injured when handling fuel.

- Stop the engine and keep heat, sparks and flame away.
- Handle fuel only outdoors.
- Wipe up spills immediately.

(cont'd)

# Storing Your Honda

---

5. To prevent rusting in the cylinders, perform the following:
  - Remove the spark plug cap from the spark plug.
  - Remove the spark plug.  
Do not connect the spark plug to the spark plug cap.
  - Pour a tablespoon (15 – 20 cm<sup>3</sup>) of clean engine oil into cylinder and cover the spark plug hole with a piece of cloth.
  - With the engine stop switch in the OFF (  ) position, press the start button several times to crank the engine and distribute the oil.
  - Reinstall the spark plug and spark plug cap.
6. Remove the battery and charge it fully. Store it in an area protected from freezing temperatures and direct sunlight. Slow charge the battery (page 138 ) once a month.

## WARNING

The battery gives off explosive hydrogen gas during normal operation.

A spark or flame can cause the battery to explode with enough force to kill or seriously hurt you.

Wear protective clothing and a face shield, or have a skilled mechanic do the battery maintenance.

7. Wash and dry your ATV. Wax all painted surfaces.
8. Inflate the tyres to their recommended pressures (page 128 ).
9. Store your ATV in an unheated area, free of dampness, away from sunlight, with a minimum of daily temperature variation.
10. Place your ATV on blocks to lift both tyres off the floor.
11. Cover your ATV with a porous material. Avoid using plastic or similar non-breathing, coated materials that restrict air flow and allow heat and moisture to accumulate.

# Storing Your Honda

---

## Removal from Storage

Refer to *Safety Precautions* on page 75 .

1. Uncover and clean your ATV.
2. If your ATV has been stored for more than four months — change the engine oil (page 94 ).
3. If your ATV has been stored for more than two months — ask your Honda dealer to drain and replace the fuel.
4. Charge the battery (page 138 ) as required. Install the battery.
5. Perform a pre-ride inspection (page 31 ), then test-ride your ATV at low speeds.

# You & the Environment

---

Owning and riding an ATV can be enjoyable, but you must do your part to protect nature. When you show respect for the land, wildlife, and other people, you also help preserve the sport of off-road riding.

Following are tips on how you can be an environmentally-responsible ATV owner.

- **Tread Lightly.** Stay on existing roads and trails, avoid surfaces that are easily damaged, and ride only in areas approved for off-road vehicles.
- **Keep the Noise Down.** Loud vehicles can be offensive. Ride as quietly as possible, don't remove your spark arrester, and don't modify the muffler or any other part of your air intake and exhaust systems. Such modifications not only increase noise, they also reduce engine performance and may be illegal.
- **Choose Sensible Cleaners.** Use a biodegradable detergent when you wash your ATV. Avoid aerosol spray cleaners that contain chlorofluorocarbons (CFCs) which damage the atmosphere's protective ozone layer. Don't throw cleaning solvents away; see the following guidelines for proper disposal.
- **Recycle Wastes.** It's illegal and thoughtless to put used engine oil in the trash, down a drain, or on the ground. Used oil, petrol, and cleaning solvents contain poisons that can hurt refuse workers and contaminate our drinking water, lakes, rivers, and oceans. Before changing your oil, make sure you have the proper containers. Put oil and other toxic wastes in separate sealed containers and take them to a recycling center. Call your local or state office of public works or environmental services to find a recycling center in your area, and to get instructions on how to dispose of non-recyclable wastes.

# Taking Care of the Unexpected

---

With all the challenges you can encounter off-road, there's a chance that sometime something may go wrong. This section gives practical advice to help you deal with a wide range of problems. Take time to read this section before you ride. Also review the tips in *Preparing for a Ride* (page 146).

General Guidelines.....	156
If Your Engine Quits or Won't Start.....	158
If You Have a Flat Tyre .....	161
If a Fuse Blows .....	164
If You Crash.....	166
If You Lose Your Key .....	167
If a Component Fails.....	168



# Taking Care of the Unexpected

---

## General Guidelines

Keeping your ATV well-maintained is the best way to reduce the possibility of having a problem while riding. However, problems can arise even with well-maintained machines.

Remember to take along your owner's manual, the tool kit that came with your ATV, and any other items (such as tyre repair supplies and additional tools) that might help you solve a problem on your own.

If something goes wrong during a ride, the first thing to do is stop as soon as you safely can. Do not continue riding if you have a flat tyre, or you hear an unusual noise, or your ATV just doesn't feel right. If you continue riding, you could cause more damage and endanger your own safety.

After a stop, take time to assess the situation. Carefully inspect your ATV to identify the problem, then consider your options before you decide what to do.

If a problem is relatively minor and you have the tools, supplies, and skills to make a permanent repair, you may be able to fix it on the trail and continue riding. Or, you may be able to make a temporary repair that allows you to slowly ride back to your base where you can make a permanent repair or get help.

When a problem is more serious — or you don't have the tools, supplies, experience, or time to deal with it — you need to choose the safest way to get yourself and your ATV back to base. For example, if you are close enough, you (or you and another person) might be able to push it back.

# **Taking Care of the Unexpected**

---

Should you ever have a problem while riding, please follow these guidelines:

- Always put personal safety first.
- Take time to assess the situation and your options before deciding what to do.
- If the problem is relatively minor and you have the tools, supplies, and skills to make a temporary repair, be sure to have permanent repairs made as soon as possible.
- Do not continue riding if you are hurt or your ATV is not in safe riding condition.

Additional recommendations for specific problems follow.

# If Your Engine Quits or Won't Start

---

Proper operation and maintenance can prevent starting and engine performance problems. In many cases, the cause of the problem may be a simple operational oversight.

If you have a problem starting the engine — or experience poor engine performance — the following information may help you. If you can't correct the problem, see your Honda dealer.

If your ATV won't start, listen as you press the start button. If you don't hear the starter motor turning, refer to the *Starter motor doesn't operate* symptom. If you can hear the starter motor working normally, refer to the *Starter motor works, but the engine won't start* symptom.

# If Your Engine Quits or Won't Start

SYMPTOM: <b>Starter motor doesn't operate.</b>	
POSSIBLE CAUSE	WHAT TO DO
ignition switch OFF	Turn the ignition switch ON.
engine stop switch OFF	Turn the engine stop switch to RUN.
transmission not in neutral	Shift into neutral.
blown fuse	Replace with a new fuse of the same rating (page 164 ).
battery lead loose	Tighten the battery lead. Charge the battery (page 138). If charging doesn't help, see your Honda dealer.
faulty starter motor	If all possible causes are negative, the starter motor may be faulty. See your Honda dealer.

SYMPTOM: <b>Starter motor works, but the engine won't start.</b>	
POSSIBLE CAUSE	WHAT TO DO
out of fuel	Fill the fuel tank.
flooded engine	See <i>Flooded Engine</i> (page 50 ).
loose or unconnected spark plug cap	Install the spark plug cap securely. If the engine still won't start, see your Honda dealer.
loose battery cables	Tighten the battery terminal bolts.
weak battery	Charge the battery (page 138 ). If charging doesn't help, see your Honda dealer.

# If Your Engine Quits or Won't Start

SYMPTOM: Engine starts, but runs poorly.	
POSSIBLE CAUSE	WHAT TO DO
idles roughly, too fast, stalls	Check engine idle adjustment (page 108 ). If the problem persists, see your Honda dealer.
poor engine performance at altitudes above 1,000 m.	Ask your Honda dealer to modify the carburetion with a high altitude jet. Refer to <i>High Altitude Carburetor Adjustment</i> , page 177.
runs erratically, misfires	See your Honda dealer.
blubbers (rich fuel mixture)	See your Honda dealer.
sooty exhaust (rich fuel mixture)	See your Honda dealer.
detonates or pings under load	If applicable, switch to the recommended octane petrol (page 87 ) or change your brand of petrol. If the problem persists, see your Honda dealer.
afterfires (backfires)	See your Honda dealer.
pre-ignition (runs on after ignition switched OFF)	See your Honda dealer.

# If You Have a Flat Tyre

---

How you handle a flat tyre on the trail depends on how serious the tyre damage is, and what tools and supplies you have with you.

If you have a slow leak or a minor puncture, use the plug method to make a temporary repair. (The plug method is applied from the outside of the tyre and is the same as that for conventional tubeless tyres.)

A plug-type repair kit, available at most auto parts stores or service stations, provides a plug, an installation tool, tyre cement, and an instruction sheet. Follow the instructions provided with the repair kit to make a temporary repair.

As soon as possible, have the tyre permanently repaired by your Honda dealer. Any tyre that cannot be repaired should be replaced.

Whenever the ATV is to be operated far from service facilities or available transportation, we recommend that you carry a tyre pump and a repair kit with the vehicle.

If the leak is more serious, or a temporary repair doesn't hold, the tyre must be replaced. The tyre will also need to be replaced if it is damaged (page 132). Replacing a tyre involves removing and re-installing the wheel (page 162).


If you are unable to repair a flat tyre on the trail, you will need to send for help. We strongly recommend that you do not try to ride with a flat tyre. The ATV will be hard to handle, and if the tyre comes off the rim, it may lock up the wheel and cause you to crash.

# If You Have a Flat Tyre


---

## Emergency Wheel Removal/Installation

Refer to *Safety Precautions* on page 75 .



(1) wheel nuts



(2) wheel rim

### Removal

1. Park your ATV on a firm, level surface.
2. Raise the front (or rear) wheels off the ground and place a support block under the vehicle.
3. Remove the wheel nuts ( 1 ) with a 17 mm socket wrench.
4. Remove the wheel.

# If You Have a Flat Tyre

---

## Installation

1. Position the wheel.
2. Position the wheel nuts so that the tapered sides face the wheel rim (2).
3. Tighten the wheel nuts in a crisscross (rather than a circular) pattern to the specified torque:  
**64 N•m ( 6.5 kgf•m, 47 lbf•ft )**

If a torque wrench was not used for installation, see your Honda dealer as soon as possible to verify proper assembly. Improper assembly may lead to loss of braking capability.




# If a Fuse Blows

---

All of the electrical circuits on your ATV have fuse to protect them from damage caused by excess current flow (short circuit or overload).

If something electrical on your ATV stops working, the first thing you should check for is a blown fuse (1).

Check the fuse before looking elsewhere for another possible cause of the problem. Replace a blown fuse and check component operation.



(1) blown fuse

The fuse is located in the battery compartment.

The spare fuse is located in the storage box under the seat.

## Recommended Fuse


main fuse	15 A
-----------	------

# If a Fuse Blows

---

## Main Fuse Access

### UNDER SEAT



(1) fuse holder assembly

(2) fuse holder

1. To prevent an accidental short circuit, turn the ignition switch OFF (  $\bigcirc$  ) before checking or replacing the fuses.
2. To access the fuse, remove the seat (page 86 ).
3. Remove the fuse holder assembly ( 1 ).
4. Pull the old fuse out of the fuse holder ( 2 ).
5. Push the new fuse in to the fuse holder.
6. Install the fuse holder assembly and seat.

# If You Crash

---

Personal safety is your first priority after an accident. If you or anyone else has been injured, take time to assess the severity of the injuries and whether it is safe to continue riding. If you cannot ride safely, send someone for help. Do not ride if you will risk further injury.

If you decide you are capable of riding safely, carefully inspect your ATV for damage and determine if it is safe to ride. Check the tightness of critical nuts and bolts securing such parts as the handlebar, control levers, brakes, and wheels.

If there is minor damage, or you are unsure about possible damage but decide to try riding the ATV back to your base, ride slowly and cautiously.

Sometimes, crash damage is hidden or not immediately apparent. When you get home, thoroughly check your ATV and correct any problems you find. Also, be sure to have your Honda dealer check the frame and suspension after any serious crash.


# If You Lose Your Key

---

Be sure to record your key number ( 1 ) at following space. You'll need this number to have a duplicate key made.

If you lose your key and aren't carrying a duplicate, either get your spare or have one made. If you don't know your key number, call the dealer you purchased your Honda from. They may have it listed in their records. If they don't, transport your ATV to them or the nearest Honda dealer. The dealer will probably have to remove the ignition switch assembly to find the key number so they can make a key for you.

KEY NO. \_\_\_\_\_



(1) key number

# If a Component Fails

---

The brake levers or pedal, control cables, and other components can be damaged as you ride in dense brush or over rocky terrain. Making a trailside repair depends on how serious the damage is and what tools and supplies you have with you.

- If any component of the brake system is damaged, you may be able to ride carefully back to your base using the other brake components for slowing or stopping.
- If you damage a throttle cable or other critical component, your ATV may be unsafe to ride. Carefully assess the damage and make any repairs that you can. But if there is any doubt, it's best to be conservative and safe.

# Technical Information

---

This section contains dimensions, capacities, and other technical data, plus information on government requirements and how to break-in your ATV.

Vehicle Identification.....	170
Specifications .....	172
Break-in Guidelines .....	176
High Altitude Carburetor Adjustment.....	177
Petrol Containing Alcohol.....	178

# Vehicle Identification

---


## Serial Numbers

The frame and engine serial numbers and key number may be required when ordering replacement parts. Record the numbers here for your reference.

The frame number (1) is stamped on the front of the frame.

FRAME NO. \_\_\_\_\_

FRONT




(1) frame number

The engine number (2) is stamped on the right side of the crankcase.

ENGINE NO. \_\_\_\_\_

RIGHT SIDE



(2) engine number

# Vehicle Identification

---

## Colour Label & Code


The colour label ( 1 ) is attached to the frame under the seat. Remove the seat (page 86 ) to check the label.

The colour code is helpful when ordering replacement parts. Record the colour and code here for your reference.

COLOUR \_\_\_\_\_

CODE \_\_\_\_\_

UNDER SEAT



(1) colour label



# Specifications

---

<b>Dimensions</b>	
overall length	1,735 mm (68.3 in)
overall width	1,062 mm (41.8 in)
overall height	1,073 mm (42.2 in)
wheelbase	1,124 mm (44.3 in)
ground clearance	149 mm (5.9 in)

<b>Weight</b>	
dry weight	161 kg (355 lbs)

<b>Fuel &amp; Lubricants</b>	
fuel recommendation	unleaded petrol, pump octane number of 86 or higher
fuel tank capacity	10.2 ℓ (2.69 US gal , 2.24 Imp gal) including reserve
fuel tank reserve	2.5 ℓ (0.66 US gal , 0.55 Imp gal)
engine oil capacity	after disassembly: 1.9 ℓ (2.0 US qt , 1.7 Imp qt) after draining: 1.6 ℓ (1.7 US qt , 1.4 Imp qt)
engine oil recommendation	API Service Classification SE, SF or SG. Honda 4-stroke oil or an equivalent.

# Specifications

## Capacities

passenger capacity	operator only
maximum weight	110 kg (243 lbs)
capacity	rider, all cargo and accessories

## Engine Specifications

displacement	229 cm <sup>3</sup> (14.0 cu-in)
bore & stroke	68.5 × 62.2 mm (2.70 × 2.45 in)
compression ratio	9.2 : 1
spark plug (standard)	DPR8EA-9 (NGK) or X24EPR-U9 (DENSO)
spark plug (cold climate)	DPR7EA-9 (NGK) or X22EPR-U9 (DENSO)
spark plug gap	0.8–0.9 mm (0.03–0.04 in)
valve clearance (cold)	0.13 mm (0.005 in)
idle speed	1,400 ± 100 min <sup>-1</sup> (rpm)

## Power Transmission

primary reduction	3.086
gear ratio, 1st	2.846
2nd	1.933
3rd	1.444
4th	1.130
5th	0.913
final reduction	3.692
final drive	shaft
reverse gear ratio	4.769

# Specifications

Chassis & Suspension		
caster		9.0°
trail		40 mm (1.6 in)
tyre size, front		AT22 × 7-10 ★★
tyre size, rear		AT22 × 10-9 ★
tyre pressure, front & rear (cold)	front	30 kPa (0.30 kgf/cm <sup>2</sup> , 4.4 psi)
	rear	20 kPa (0.2 kgf/cm <sup>2</sup> , 2.9 psi)
maximum tyre pressure, front & rear (cold)	front	34 kPa (0.34 kgf/cm <sup>2</sup> , 5.0 psi)
	rear	23 kPa (0.23 kgf/cm <sup>2</sup> , 3.3 psi)
minimum tyre pressure, front & rear (cold)	front	26 kPa (0.26 kgf/cm <sup>2</sup> , 3.8 psi)
	rear	17 kPa (0.17 kgf/cm <sup>2</sup> , 2.5 psi)

Electrical	
battery	12 V – 8 Ah
generator	0.123 kW/5,000 min <sup>-1</sup> (rpm)

Lights	
headlight (Low/High)	12 V 35/35 W
tail light	12 V – 5 W
neutral indicator	12 V – 1.7W
reverse indicator	12 V – 1.7W

# Specifications

---

<b>Fuse</b>	
main	15 A

<b>Torque Specification</b>	
oil drain bolt	25 N·m (2.5 kgf·m , 18 lbf·ft)
rear final gear case oil drain bolt	12 N·m (1.2 kgf·m , 9 lbf·ft)
wheel nuts	64 N·m (6.5 kgf·m , 47 lbf·ft)

# Break-in Guidelines

---

Help assure your ATV's future reliability and performance by paying extra attention to how you ride during the first operating day or 25 km (15 miles).

During this period, avoid full-throttle starts and rapid acceleration.

# High Altitude Carburetor Adjustment

---

Your engine's air-fuel mixture becomes overly rich when operated at high altitudes. Above 1,000 m (3,000 feet), a rich mixture can cause driveability problems, reduce engine performance, and increase fuel consumption. To compensate, you can have the carburetor adjusted for high altitude riding. See your Honda dealer.

A high altitude jet is available to compensate for high altitude richness. For those who are mechanically proficient and have the necessary tools, installation and adjustment procedures are given in the official Honda Shop Manual available from your Honda dealer. All others should have this carburetor modification performed by a Honda dealer.

However, the carburetor must be returned to standard factory specifications before riding again at lower altitudes (below 1,500 m, 5,000 feet).

Sustained riding at lower altitudes with the lean high-altitude setting may cause rough idling, stalling, or engine damage from overheating.

Altitude range	Main jet	Pilot screw
0 – 1,500 m (0 – 5,000 feet)	No. 95	Factory preset
1,000 – 2,500 m or higher (3,000 – 8,000 feet)	No. 92	Screw in 1/8 turn clockwise from factory preset

# Petrol Containing Alcohol

---

If you decide to use a petrol containing alcohol (gasohol), be sure its octane rating is at least as high as that recommended above.

There are two types of gasohol: One contains ethanol, and the other contains methanol. Do not use gasohol that contains more than 10% ethanol. Do not use gasohol that contains methanol (methyl or wood alcohol) unless it also contains cosolvents and corrosion inhibitors for methanol. Never use petrol containing more than 5% methanol, even if it has cosolvents and corrosion inhibitors.

Engine performance problems resulting from the use of fuels that contain alcohol are not covered under the warranty. Honda cannot endorse the use of fuels containing methanol since evidence of their suitability is not yet complete.

Before buying fuel from an unfamiliar station, try to find out if the fuel contains alcohol. If it does, confirm the type and percentage of alcohol used. If you notice any undesirable operating symptoms while using a petrol that contains alcohol, or one that you think contains alcohol, switch to a petrol that you know does not contain alcohol.

# Table of Contents

---

The following presents the contents of each section of your owner’s manual.

**ATV SAFETY ..... 1**  
Important Safety Information ..... 2  
Safety Labels..... 5

**INDICATORS & CONTROLS..... 9**  
Component Locations ..... 11  
Indicators..... 14  
    Reverse and Neutral Indicator Lamps .....14



# Table of Contents

---

Controls & Features .....	15
Fuel Valve .....	15
Choke Knob .....	16
Ignition Switch .....	17
Start Button .....	18
Engine Stop Switch .....	18
Headlight Switch .....	19
Headlight Dimmer Switch .....	19
Throttle lever .....	20
Reverse Selector Knob .....	21
Front Brake Lever .....	22
Rear Brake Lever .....	22
Rear Brake Pedal .....	22
Parking Brake .....	22
Flag Pole Bracket .....	23
<b>BEFORE RIDING .....</b>	<b>25</b>
Are You Ready to Ride ? .....	26
Protective Apparel .....	26
Rider Training .....	28
Age Recommendation .....	29
No Passengers .....	29
No Alcohol or Drugs .....	30
Is Your ATV Ready to Ride ? .....	31
Pre-ride Inspection .....	31
Load Limits & Guideline .....	34
Loading .....	34

# Table of Contents

---

<b>BASIC OPERATION &amp; RIDING .....</b>	<b>39</b>
Safe Riding Precautions .....	41
Off-Road Use Only .....	41
Keep Hands and Feet on Controls.....	42
Control Speed.....	43
Use care on Unfamiliar or Rough Terrain.....	44
Do Not Perform Stunts.....	45
Starting & Stopping the Engine .....	46
Preparation .....	46
Starting Procedure .....	47
Flooded Engine .....	50
How to Stop the Engine .....	50
Shifting Gears .....	51
Riding in Reverse .....	53
Braking.....	55
Riding Your ATV .....	57
Making Turns.....	57
Skidding or Sliding .....	59
Riding Up Hills .....	60
Riding Down Hills .....	64
Crossing or Turning on Hills or Slopes.....	65
Riding Over Obstacles .....	67
Riding Through Water .....	68
Parking .....	69

# Table of Contents

---

<b>SERVICING YOUR HONDA.....</b>	<b>71</b>
<i>Before You Service Your Honda</i>	
The Importance of Maintenance .....	73
Maintenance Safety .....	74
Important Safety Precautions .....	75
Maintenance Schedule .....	76
Maintenance Record.....	80
 <i>Service Preparations</i>	
Component Locations .....	81
Tool Kit.....	84
Owner's Manual Storage.....	85
Seat Removal .....	86
 <i>Service Procedures</i>	
<u>Fluids &amp; Filters</u>	
Fuel .....	87
Engine oil .....	90
Gear Case Oil .....	96
Air Cleaner .....	98
 <u>Engine</u>	
Throttle.....	103
Carburetor Choke Cable & Knob.....	105
Clutch System .....	106
Engine Idle Speed and Air-Fuel Mixture .....	108
Spark Plug.....	110
Valves.....	113
Spark Arester.....	114

(cont'd)

# Table of Contents

---

## Chassis

Brakes.....	116
Tyres .....	126
Engine Guard & Skid Plates.....	133

## Electrical

Battery .....	134
---------------	-----

Appearance Care .....	139
-----------------------	-----

## **TIPS..... 145**

Preparing for a Ride .....	146
What to Take to The Riding Area .....	146
What to Take on The Trail .....	147
Transporting Your Honda .....	148
Storing Your Honda .....	150
You & the Environment .....	154

## **TAKING CARE OF THE UNEXPECTED..... 155**

General Guidelines.....	156
If Your Engine Quits or Won't Start.....	158
If You Have a Flat Tyre .....	161
If a Fuse Blows .....	164
If You Crash.....	166
If You Lose Your Key .....	167
If a Component Fails.....	168

# Table of Contents

---

<b>TECHNICAL INFORMATION.....</b>	<b>169</b>
Vehicle Identification.....	170
Specifications.....	172
Break-in Guidelines .....	176
High Altitude Carburetor Adjustment.....	177
Petrol Containing Alcohol.....	178
 <b>TABLE OF CONTENTS.....</b>	 <b>180</b>
 <b>INDEX.....</b>	 <b>186</b>

# Index

---

## A

accessories.....	37
age recommendation .....	29
air cleaner,	
filter.....	99
housing drain tube .....	102
air pressure,	
gauge.....	84
tyre .....	127
altitude, high.....	177
apparel, protective .....	26
appearance care .....	139

## B

Battery .....	134
Brakes,	
cables.....	124
draining water from.....	125
fluid.....	116
front brake lever .....	22
front brake pads .....	119
parking .....	69

# Index

---

rear brake lever.....	22
rear brake lever freeplay .....	122
rear brake pedal .....	22
rear brake pedal freeplay.....	120
shoe lining clearance .....	124
shoe wear.....	124
braking .....	55
break-in guidelines .....	176

## C

capacity, fuel .....	88
carburetor, altitude adjustment .....	177
care, appearance .....	139
choke,	
cable .....	105
knob.....	105
cleaning, appearance care.....	139
climbing hills.....	60
clutch system.....	106
colour label.....	171
compartment,	
owner's manual .....	85
tool kit .....	84

(cont'd)

# Index

---

component fails .....	168
component locations,	
indicators and controls .....	11
maintenance .....	80
crash, if you.....	166
crossing or turning on hills or slopes .....	65

<b>D</b>
----------

dimmer switch, headlight .....	19
dipstick .....	93



## E

engine	
flooded .....	50
guard .....	133
idle speed.....	108
number .....	170
oil .....	90
pinging .....	87
starting.....	48
stop switch.....	18
stopping.....	50
won't start .....	158
environment .....	154
exhaust system	
cleaning .....	32
purging .....	114

## F

flag pole bracket.....	23
flat tyre .....	161
flooded engine.....	50
frame number .....	170

(cont'd)

# Index

---

fuel,	
fill cap .....	88
high altitude fuel mixture adjustment.....	177
recommendation.....	87
refueling .....	88
reserve fuel supply .....	15
tank capacity .....	88
valve.....	15
fuses .....	164

## G

gap, spark plug .....	111
gear case oil.....	96
gear shifting .....	51

## H

headlight dimmer switch .....	19
headlight switch .....	19
high altitude carburetor adjustment.....	177

hills,	
crossing or turning on slopes .....	65
riding down hills .....	64
riding up hills .....	60
stopping on hills .....	62

## I

identification, vehicle.....	170
idle speed, engine .....	108
ignition switch.....	17
indicators	
neutral indicator .....	14
reverse indicator .....	14
inspection, pre-ride.....	31

## K

key,	
lost.....	167
number .....	167
kit, tool .....	84

# Index

---

## L

labels, safety.....	5
limit, weight .....	35
load limits.....	35
loading guidelines .....	36
location, components,	
indicators & display .....	11
maintenance .....	81
lubrication	
engine oil.....	90
gear case oil.....	96

## M

maintenance,	
importance.....	73
precautions .....	75
record .....	80
safety .....	74
schedule.....	76

maximum weight limit .....	35
modifications.....	38

## N

neutral indicator .....	14
numbers, serial .....	170

## O

obstacles, riding over .....	67
oil,	
engine .....	90
gear case .....	96
operating controls.....	15
owner's manual storage.....	85

# Index

---

## P

parking .....	69
passenger, no carrying.....	29
pavement, no riding on.....	3
petrol .....	87
petrol containing alcohol.....	178
pinging, engine.....	87
plugs, spark .....	110
pre-ride inspection.....	31
problems, unexpected.....	155
protective apparel .....	26

## R

removal, seat .....	86
reverse,	
assist cable.....	107
assist lever .....	107
gear, shifting into .....	51
indicator .....	14
riding in .....	53
selector knob .....	21
rider training.....	28

riding,	
basic operations .....	39
clothing .....	26
precautions .....	75
preparing for .....	31
over obstacles .....	67
safety .....	2
safety precautions.....	41
through water .....	68

<b>S</b>
----------

safety,	
important precautions.....	75
labels .....	6
riding precautions.....	41
schedule, maintenance.....	76
seat removal .....	86
serial numbers .....	170

(cont'd)

# Index

---

shifting gears .....	51
skid plates.....	133
skidding or sliding .....	59
spark arrester .....	114
spark knock .....	87
spark plug.....	110
specifications.....	172
stalling on a hill .....	62
start button.....	18
starting,	
engine .....	46
troubleshooting.....	158
stop switch, engine .....	18
stopping engine .....	50
storage,	
ATV .....	150
owner's manual .....	85
switch,	
headlight.....	19
headlight dimmer .....	19
ignition .....	17



## T

throttle	
lever.....	20, 103
tyres,	
air pressure .....	127
flat .....	163
replacing.....	132
repairing .....	131
specifications.....	132
thread conditions .....	130
tool kit .....	84
training, rider.....	28
transporting your ATV .....	148
trouble, unexpected .....	155
troubleshooting, starting.....	159
turning,	
on level ground.....	58
on hills or slopes.....	65

## V

valve, fuel.....	15
valve clearance .....	113

# Index

---

## W

warning labels .....	6
water,	
riding through.....	68
draining from brakes .....	125
weight limit .....	35
wheel removal .....	162

# HONDA

The power of dreams.

## WARNING

The improper operation of ATVs may result in severe injury or death

- Read the owner's Manual.
- Follow all warnings and instructions.
- Never use without proper training and instruction.

While riding :

- Never ride too fast for your skills or the conditions.
- Always use proper riding techniques for hills, slopes and rough terrain.
- Use care when changing riding surfaces. ATVs handle differently on different surfaces, such as sand, dirt, or pavement.



- Never carry a passenger, since it would affect balance and steering and may cause you to lose control.



- Avoid operating on public roads, since a collision can occur with another vehicle.



- Never ride after drinking alcohol or using drugs.



- Always wear a helmet, eye protection, and protective gear.